

Revision Date: 10 Feb 2023

Page 1 of 8

# SAFETY DATA SHEET

### **SECTION 1**

### PRODUCT AND COMPANY IDENTIFICATION

### **PRODUCT**

Product Name: MOBIL SHC AWARE GREASE EP 2
Product Description: Synthetic Base Stocks and Additives

**Product Code:** 20154030A610

Intended Use: Grease

### **COMPANY IDENTIFICATION**

Supplier: PT. ExxonMobil Lubricants Indonesia

Wisma GKBI, 27th Floor Jl. Jend Sudirman No. 28 Jakarta 10210 Indonesia Or ExxonMobil Affiliates

**24 Hour Health Emergency** 001-803-017-9114 / +1-703-527-3887

**Supplier General Contact** 6221-525-1883

**FAX** 62-21-571-5171

# **SECTION 2**

# **HAZARDS IDENTIFICATION**

This material is not hazardous according to regulatory guidelines (see (M)SDS Section 15).

### Other hazard information:

### PHYSICAL / CHEMICAL HAZARDS

No significant hazards.

### **HEALTH HAZARDS**

High-pressure injection under skin may cause serious damage. Excessive exposure may result in eye, skin, or respiratory irritation.

### **ENVIRONMENTAL HAZARDS**

No significant hazards.

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.



Revision Date: 10 Feb 2023

Page 2 of 8

### **SECTION 3**

### **COMPOSITION / INFORMATION ON INGREDIENTS**

This material is defined as a mixture.

Hazardous Substance(s) or Complex Substance(s) required for disclosure

| Name  | CAS#         | Concentration* | GHS Hazard Codes        |
|---|--------------|----------------|-------------------------|
| ALKYL NAPHTHALENE SULFONIC ACID, CALCIUM SALT |              | 1 - < 5%       | H319(2A)                |
|   | CONFIDENTIAL |                |                         |
| CARBONIC ACID, CALCIUM SALT (1:1)             | 471-34-1     | 1 - < 5%       | None                    |
| REACTION PRODUCTS OF DIHYDRO-3-               |              | 0.1 - < 1%     | H302, H315, H318, H402, |
| (TETRAPROPENYL)FURAN-2,5 DIONE WITH PROPANE-  | CONFIDENTIAL |                | H412                    |
| 1,2,DIOL                                      |              |                |                         |

<sup>\*</sup> All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

### **SECTION 4**

#### **FIRST AID MEASURES**

### **INHALATION**

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

### **SKIN CONTACT**

Wash contact areas with soap and water. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

#### **EYE CONTACT**

Flush thoroughly with water. If irritation occurs, get medical assistance.

#### **INGESTION**

First aid is normally not required. Seek medical attention if discomfort occurs.

#### **NOTE TO PHYSICIAN**

None

### **SECTION 5**

# **FIRE FIGHTING MEASURES**

### **EXTINGUISHING MEDIA**

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water

### **FIRE FIGHTING**

**Fire Fighting Instructions:** Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Hazardous Combustion Products: Oxides of carbon, Smoke, Fume



Revision Date: 10 Feb 2023

Page 3 of 8

### FLAMMABILITY PROPERTIES

Flash Point [Method]: >250°C (482°F) [EST. FOR OIL, ASTM D-92 (COC)] Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

Autoignition Temperature: N/D

### **SECTION 6**

### **ACCIDENTAL RELEASE MEASURES**

### **NOTIFICATION PROCEDURES**

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

#### **PROTECTIVE MEASURES**

Avoid contact with spilled material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

### SPILL MANAGEMENT

Land Spill: Scrape up spilled material with shovels into a suitable container for recycle or disposal.

**Water Spill:** Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Skim from surface.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

### **ENVIRONMENTAL PRECAUTIONS**

Prevent entry into waterways, sewers, basements or confined areas.

### **SECTION 7**

### HANDLING AND STORAGE

### **HANDLING**

Prevent small spills and leakage to avoid slip hazard.

**Static Accumulator:** This material is not a static accumulator.

### **STORAGE**

Do not store in open or unlabelled containers. Keep away from incompatible materials.

# **SECTION 8**

# **EXPOSURE CONTROLS / PERSONAL PROTECTION**

# **Biological limits**

No biological limits allocated.



Revision Date: 10 Feb 2023

Page 4 of 8

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

### **ENGINEERING CONTROLS**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

#### PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No protection is ordinarily required under normal conditions of use and with adequate ventilation. Particulate

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

No protection is ordinarily required under normal conditions of use. Nitrile, Viton

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

#### **ENVIRONMENTAL CONTROLS**

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.



Revision Date: 10 Feb 2023

Page 5 of 8

### **SECTION 9**

### **PHYSICAL AND CHEMICAL PROPERTIES**

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

### **GENERAL INFORMATION**

Physical State: Solid
Form: Semi-fluid
Color: Brown
Odor: Characteristic
Odor Threshold: N/D

### IMPORTANT HEALTH, SAFETY, AND ENVIRONMENTAL INFORMATION

Relative Density (at 15 °C): 0.96 [Typical]

Flammability (Solid, Gas): N/A

Flash Point [Method]: >250°C (482°F) [EST. FOR OIL, ASTM D-92 (COC)] Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

Autoignition Temperature: N/D
Boiling Point / Range: N/D
Decomposition Temperature: N/D
Vapor Density (Air = 1): N/D
Vapor Pressure: N/D

Evaporation Rate (n-butyl acetate = 1): N/D

pH: N/A

Log Pow (n-Octanol/Water Partition Coefficient): N/D

Solubility in Water: Negligible

Viscosity: 298 cSt (298 mm2/sec) at 40 °C - 352 cSt (352 mm2/sec) at 40 °C

**Oxidizing Properties:** See Hazards Identification Section.

OTHER INFORMATION

Freezing Point: N/D Melting Point: N/D

NOTE: Most physical properties above are for the oil component in the material.

#### SECTION 10 STABILITY AND REACTIVITY

STABILITY: Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Excessive heat. High energy sources of ignition.

MATERIALS TO AVOID: Strong oxidizers

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

### SECTION 11 TOXICOLOGICAL INFORMATION

# **INFORMATION ON TOXICOLOGICAL EFFECTS**



Revision Date: 10 Feb 2023

Page 6 of 8

| Hazard Class   | Conclusion / Remarks   |
|--|--|
| Inhalation   |  |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.  |
| Irritation: No end point data for material.                    | Negligible hazard at ambient/normal handling temperatures.   |
| Ingestion  |  |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.  |
| Skin   |  |
| Acute Toxicity: No end point data for material.                | Minimally Toxic. Based on assessment of the components.  |
| Skin Corrosion/Irritation: No end point data for material.     | Negligible irritation to skin at ambient temperatures. Based on assessment of the components.                  |
| Eye  |  |
| Serious Eye Damage/Irritation: No end point data for material. | May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.                       |
| Sensitization  |  |
| Respiratory Sensitization: No end point data for material.     | Not expected to be a respiratory sensitizer.   |
| Skin Sensitization: No end point data for material.            | Not expected to be a skin sensitizer. Based on assessment of the components.                                   |
| Aspiration: Data available.                                    | Not expected to be an aspiration hazard. Based on physico-<br>chemical properties of the material.             |
| <b>Germ Cell Mutagenicity:</b> No end point data for material. | Not expected to be a germ cell mutagen. Based on assessment of the components.                                 |
| Carcinogenicity: No end point data for material.               | Not expected to cause cancer. Based on assessment of the components.   |
| <b>Reproductive Toxicity:</b> No end point data for material.  | Not expected to be a reproductive toxicant. Based on assessment of the components.                             |
| Lactation: No end point data for material.                     | Not expected to cause harm to breast-fed children.   |
| Specific Target Organ Toxicity (STOT)                          |  |
| Single Exposure: No end point data for material.               | Not expected to cause organ damage from a single exposure.   |
| Repeated Exposure: No end point data for material.             | Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components. |

### OTHER INFORMATION

# Contains:

Synthetic base oils: Not expected to cause significant health effects under conditions of normal use, based on laboratory studies with the same or similar materials. Not mutagenic or genotoxic. Not sensitizing in test animals and humans.

### IARC Classification:

The following ingredients are cited on the lists below: None.

-- REGULATORY LISTS SEARCHED--

1 = IARC 1 2 = IARC 2A 3 = IARC 2B

SECTION 12 ECOLOGICAL INFORMATION



Revision Date: 10 Feb 2023

Page 7 of 8

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

### **ECOTOXICITY**

Material -- Not expected to be harmful to aquatic organisms.

### **MOBILITY**

Base oil component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

#### **SECTION 13**

#### **DISPOSAL CONSIDERATIONS**

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

### **DISPOSAL RECOMMENDATIONS**

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

# **SECTION 14**

### TRANSPORT INFORMATION

**LAND**: Not Regulated for Land Transport

SEA (IMDG): Not Regulated for Sea Transport according to IMDG-Code

Marine Pollutant: No

AIR (IATA): Not Regulated for Air Transport

### **SECTION 15**

### REGULATORY INFORMATION

This material is not considered hazardous according to Minister of Industry of the Republic of Indonesia Regulation Concerning The Globally Harmonized System of Classification and Labelling of Chemicals.

# REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

Listed or exempt from listing/notification on the following chemical inventories : AllC, DSL, ENCS, IECSC, ISHL, KECI, PICCS, TCSI, TSCA



Revision Date: 10 Feb 2023

Page 8 of 8

# **SECTION 16**

### OTHER INFORMATION

# N/D = Not determined, N/A = Not applicable

**KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):** 

H302: Harmful if swallowed; Acute Tox Oral, Cat 4 H315: Causes skin irritation; Skin Corr/Irritation, Cat 2

H318: Causes serious eye damage; Serious Eye Damage/Irr, Cat 1 H319(2A): Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2A

H402: Harmful to aquatic life; Acute Env Tox, Cat 3

H412: Harmful to aquatic life with long lasting effects; Chronic Env Tox, Cat 3

### THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

No revision information

------

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

\_\_\_\_\_\_

DGN: 7123938XID (1021009)

\_\_\_\_\_\_