

Revision Date: 30 Mar 2021

Page 1 of 13

# MATERIAL SAFETY DATA SHEET

MSDS No.: N/A

# SECTION 1

# PRODUCT AND COMPANY IDENTIFICATION

A. Product Name: UNIVIS HVI 13

Product Description: Hydrocarbons and Additives

**Product Code:** 201560109720

B. Recommended Use of Product and Restrictions in Use.

Recommended use of the product: Hydraulic fluids and additives

Restrictions in Use: This product is not recommended for any industrial, professional or

consumer use other than the identified uses above.

# C. Manufacturer/Supplier information:

For details contact

Mobil Korea Lube Oil Inc.

Level 22, Seoul Square bd., 416 Hangang-daero, Jung-gu, Seoul Republic of Korea

Emergency Response Number	00-308-13-2549 / +1-703-527-3887		
Supplier General Contact	82-2-750-8700		
FAX	82-2-750-8751		

# SECTION 2 HAZARDS IDENTIFICATION

This material is hazardous according to regulatory guidelines (see (M)SDS Section 15).

### A. Hazard Classification:

Acute inhalation toxicant: Category 4. Skin irritation: Category 2. Aspiration toxicant: Category 1. Chronic aquatic toxicant: Category 2.

B. Label Elements Including Precautionary Statements:

# Hazard Pictogram:





Revision Date: 30 Mar 2021

Page 2 of 13



Signal Word: Danger

#### Hazard Statements:

Health: H304: May be fatal if swallowed and enters airways. H315: Causes skin irritation. H332:

Harmful if inhaled.

Environmental: H411: Toxic to aquatic life with long lasting effects.

# Precautionary Statements:

Prevention: P261: Avoid breathing mist / vapours. P264: Wash skin thoroughly after handling. P271: Use only outdoors or in a well-ventilated area. P273: Avoid release to the environment. P280: Wear protective gloves.

Response: P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P302 + P352: IF ON SKIN: Wash with plenty of soap and water. P304 + P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312: Call a POISON CENTER or doctor/physician if you feel unwell. P331: Do NOT induce vomiting. P332 + P313: If skin irritation occurs: Get medical advice/ attention. P362 + P364: Take off contaminated clothing and wash it before reuse. P391: Collect spillage.

Storage: P405: Store locked up.

Disposal: P501: Dispose of contents and container in accordance with local regulations.

### C. Other Hazards Which Are Not Included In The Classification Criteria

### Physical / Chemical Hazards

No significant hazards.

#### Health Hazards

High-pressure injection under skin may cause serious damage. May be irritating to the eyes, nose, throat, and lungs.

### Environmental Hazards

No additional hazards.

NFPA Hazard ID: Health: 2 Flammability: 1 Reactivity: 0 HMIS Hazard ID: Health: 2 Flammability: 1 Reactivity: 0

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.



Revision Date: 30 Mar 2021

Page 3 of 13

### SECTION 3

### COMPOSITION / INFORMATION ON INGREDIENTS

This material is defined as a mixture.

# Hazardous Substance(s) or Complex Substance(s) required for disclosure

Name	Other Name	CAS # or ld.	Concentration*	GHS Hazard Codes
		No.		
2,6-DI-TERT-BUTYLPHENOL	_	KE-03085	0.1 - < 0.25%	H315, H400(M factor 1), H410(M factor 1)
HYDROTREATED MIDDLE DISTILLATE (PETROLEUM)	-	KE-12554	50 - < 100%	H227, H304, H332, H315, H401, H411
METHYL METHACRYLATE	-	KE-25050	0.1 - < 1%	H225, H317, H335, H315, H402

\* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

# SECTION 4

### FIRST AID MEASURES

#### A. Eve Contact

Flush thoroughly with water. If irritation occurs, get medical assistance.

## B. Skin Contact

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

### C. Inhalation

Immediately remove from further exposure. Get immediate medical assistance. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. Give supplemental oxygen, if available. If breathing has stopped, assist ventilation with a mechanical device.

# D. Ingestion

Seek immediate medical attention. Do not induce vomiting.

### E. Other note to physician

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.



Revision Date: 30 Mar 2021

Page 4 of 13

# Acute and Delayed Symptoms/Effects

See Toxicological Section

# Pre-existing Medical Conditions Which May Be Aggravated By Exposure

None.

SECTION 5

### FIRE FIGHTING MEASURES

Flammability Properties

Flash Point [Method]: 110° C (230° F) [ EN/ISO 2592]

Autoignition Temperature: N/D

Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D

### A. Suitable (and Unsuitable) Extinguishing Media

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Inappropriate Extinguishing Media: Straight Streams of Water

### B. Specific Hazards arising from the Chemical

**Unusual Fire Hazards:** Pressurized mists may form a flammable mixture. Hazardous material. Firefighters should consider protective equipment indicated in Section 8.

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke. Fume. Sulfur oxides

### C. Special Protective Equipment and Precautions for Fire-fighters

Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

# SECTION 6

# ACCIDENTAL RELEASE MEASURES

### A. Personal Precautions and Protective Equipment

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

### B. Environmental Precautions and Protective Procedure

In the event of a spill or accidental release, notify relevant authorities in accordance with all



Revision Date: 30 Mar 2021

Page 5 of 13

applicable regulations.

Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

### C. Methods and Materials for Containment and Cleaning Up

Land Spill: Stop leak if you can do it without risk. Do not touch or walk through spilled material. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

**Water Spill:** Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

### SECTION 7

### HANDLING AND STORAGE

### A. Precautions for Safe Handling

Avoid breathing mists or vapors. Avoid contact with skin. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or ground procedures. However, bonding and grounds may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Static Accumulator: This material is a static accumulator.

#### B. Conditions for Safe Storage

The type of container used to store the material may affect static accumulation and dissipation. Do not store in open or unlabelled containers.

### SECTION 8

### EXPOSURE CONTROLS AND PERSONAL PROTECTION

# A. Exposure Limit Values, Biological Limit Values

Exposure limits/standards (Note: Exposure limits are not additive)



Revision Date: 30 Mar 2021

Page 6 of 13

Substance Name	Form	Limit /	Standard	Note	Source	Year
METHYL METHACRYLATE		STEL	100 ppm		Korea OELs	2018
METHYL METHACRYLATE		TWA	50 ppm		Korea OELs	2018
METHYL METHACRYLATE		STEL	100 ppm		ACGIH	2020
METHYL METHACRYLATE		TWA	50 ppm		ACGIH	2020

Exposure limits/standards for materials that can be formed when handling this product: When mists/aerosols can occur the following is recommended: 5 mg/m³ - ACGIH TLV (inhalable fraction).

No biological limits allocated.

# B. Appropriate Engineering Controls

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Adequate ventilation should be provided so that exposure limits are not exceeded.

# C. Personal Protective Equipment

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: Half-face filter respirator Particulate

For high airborne concentrations, use an approved supplied—air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended. If contact with forearms is likely wear gauntlet style gloves. Nitrile, Viton



Revision Date: 30 Mar 2021

Page 7 of 13

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include: Chemical/oil resistant clothing is recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

### **Environmental Controls**

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

# SECTION 9

# PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

A. Appearance

Physical State: Liquid

Color: Red

- B. Odor: Characteristic
- C. Odor Threshold: N/D
- **D.** pH: N/A
- E. Melting Point: N/A Freezing Point: N/D
- F. Initial Boiling Point / Range: N/D
- **G. Flash Point [Method]:** 110° C (230° F) [ EN/ISO 2592]
- H. Evaporation Rate (n-butyl acetate = 1): N/D
- I. Flammability (Solid, Gas): N/A
- J. Flammable Limits (Approximate volume % in air): LEL: N/D UEL: N/D
- K. Vapor Pressure: N/D
- L. Solubility in Water: Negligible
- M. Vapor Density (Air = 1): N/D
- N. Relative Density (at 15 °C): 0.87
- O. Log Pow (n-Octanol/Water Partition Coefficient): N/D
- P. Autoignition Temperature: N/D
- Q. Decomposition Temperature: N/D
- **R. Viscosity:** 14.1 cSt (14.1 mm2/sec) at 40 ° C
- S. Molecular Weight: N/D

# SECTION 10

# STABILITY AND REACTIVITY



Revision Date: 30 Mar 2021

Page 8 of 13

# A. Chemical Stability and Possibility of Hazard Reactions

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

B. Conditions to Avoid: Excessive heat.

C. Incompatible Materials: Strong oxidizers

D. Hazardous Decomposition Products: Material does not decompose at ambient temperatures.

# SECTION 11

# TOXICOLOGICAL INFORMATION

# A. Information on Likely Routes of Exposure

No data available

### B. Information on Health Hazards

# Acute Toxicity (Inhalation):

Product

No end point data for material. Moderately toxic. Based on assessment of the components.

Inhalation Irritation: No end point data for material. Elevated temperatures or mechanical action may form vapors, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs.

# Acute Toxicity (Ingestion):

Product

No end point data for material. Minimally Toxic. Based on assessment of the components.

### Acute Toxicity (Dermal)

Product

No end point data for material. Minimally Toxic. Based on assessment of the components.

### Skin corrosion/irritation

Product

No end point data for material. Irritating to the skin. Based on assessment of the components.

### Serious eye damage/irritation

Product

No end point data for material. May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.

### Respiratory sensitization

Product

No end point data for material. Not expected to be a respiratory sensitizer.

### Skin sensitization

Product



Revision Date: 30 Mar 2021

Page 9 of 13

No end point data for material. Not expected to be a skin sensitizer. Based on assessment of the components.

### Carcinogenicity

Product

No end point data for material. Not expected to cause cancer. Based on assessment of the components.

### Germ cell mutagenicity

Product

No end point data for material. Not expected to be a germ cell mutagen. Based on assessment of the components.

### Reproductive toxicity

Product

No end point data for material. Not expected to be a reproductive toxicant. Based on assessment of the components.

# Specific target organ toxicity - single exposure

Product

No end point data for material. Not expected to cause organ damage from a single exposure.

# Specific target organ toxicity - repeat exposure

Product

No end point data for material. Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.

### Aspiration hazard

Product

Data available. May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material.

# Other Information

### For the product itself:

Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema. Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components, this formulation, or similar formulations.

# IARC Classification:

The following ingredients are cited on the lists below: None.

--REGULATORY LISTS SEARCHED--

1 = IARC 1 2 = IARC 2A 3 = IARC 2B

SECTION 12 ECOLOGICAL INFORMATION



Revision Date: 30 Mar 2021

Page 10 of 13

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

### A. Ecotoxicity

Material — Expected to be toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

# B. Persistence and Degradability

### Biodegradation:

Hydrocarbon component -- Expected to be inherently biodegradable

### C. Bioaccumulation

Hydrocarbon component — Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

## D. Mobility

More volatile component — Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

High molecular wt. component — Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

# E. Other adverse effects: Not applicable

# SECTION 13

# DISPOSAL CONSIDERATIONS

#### A. Disposal methods

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

### B. Disposal precautions

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Protect the environment. Dispose of used oil at designated sites. Minimize skin contact. Do not mix used oils with solvents, brake fluids or coolants.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed



Revision Date: 30 Mar 2021

Page 11 of 13

contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

#### SECTION 14

#### TRANSPORT INFORMATION

### REGULATION ON SHIP-TRANSPORTATION AND STORAGE OF DANGEROUS SUBSTANCES (SEA (IMDG))

**A. UN Number:** 3082

**B. Proper Shipping Name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrotreated Middle Distillate (Petroleum))

C. Hazard Class & Division: 9

D. Packing Group: |||
E. Marine Pollutant: Ye

F. Special Precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance: Refer to the requirement under the Classification of Transport.

**EMS Number:** F-A, S-F

Label(s): 9

**Transport Document Name:** UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Hydrotreated Middle Distillate (Petroleum)), 9, PG III

### LAND (ADR/RID)

**A. UN Number:** 3082

**B. Proper Shipping Name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Hydrotreated Middle Distillate (Petroleum))

C. Hazard Class & Division: 9

D. Packing Group: |||

E. Marine pollutants: Only applicable for sea transport

F. Special Precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance: Refer to the requirement under the Classification of Transport.

Classification Code: M6

Hazchem EAC: 3Z Hazard ID Number: 90

Label(s) / Mark(s): 9, EHS

#### AIR (IATA)

**A. UN Number:** 3082

**B. Proper Shipping Name:** ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Hydrotreated Middle Distillate (Petroleum))

C. Hazard Class & Division: 9

D. Packing Group: |||

E. Marine pollutants: Only applicable for sea transport

F. Special Precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance: Refer to the requirement under the Classification of Transport.

Label(s) / Mark(s): 9, EHS

**Transport Document Name:** UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Hydrotreated Middle Distillate (Petroleum)), 9, PG III



Revision Date: 30 Mar 2021

Page 12 of 13

\_\_\_\_\_

### SECTION 15

### REGULATORY INFORMATION

This material is considered hazardous according to Korean GHS classification criteria.

Regulatory Status and Applicable Laws and Regulations

- A. Industrial Safety & Health Act: Prohibited, Subject to an Approval for Manufacturing and Controlled Hazardous Substances: None.
- B. Chemicals Control Act: Toxic, Banned and Restricted Toxic Chemicals, Authorization substances,
  Accidental Release Prevention Substances and Priority Existing Chemicals to Registration: None.
- C. ACT ON THE SAFETY CONTROL OF HAZARDOUS SUBSTANCES: Not applicable.

D.

E. Other requirements in domestic and other countries

Listed or exempt from listing/notification on the following chemical inventories: ALIC, DSL, ENCS, KECI, PICCS, TCSI, TSCA

#### Special Cases:

Inventory		Status		
IECSC		Restrictions Apply		
ISHL		Restrictions Apply		

## SECTION 16 OTHER INFORMATION

A. Information sources and references: Sources of information used in preparing this SDS included one or more of the following: results from in house or supplier toxicology studies, CONCAWE Product Dossiers, publications from other trade associations, such as the EU Hydrocarbon Solvents REACH Consortium, U.S. HPV Program Robust Summaries, the EU IUCLID Data Base, U.S. NTP publications, and other sources, as appropriate.

В.

C. Revision number and latest revision date
Revision Date: 30 Mar 2021

D. Others



Revision Date: 30 Mar 2021

Page 13 of 13

# N/D = Not determined, N/A = Not applicable

# KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

H225: Highly flammable liquid and vapor; Flammable Liquid, Cat 2

H227: Combustible liquid; Flammable Liquid, Cat 4

H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1

H315: Causes skin irritation; Skin Corr/Irritation, Cat 2

H317: May cause allergic skin reaction; Skin Sensitization, Cat 1

H332: Harmful if inhaled; Acute Tox Inh, Cat 4

H335: May cause respiratory irritation; Target Organ Single, Resp Irr

H400: Very toxic to aquatic life; Acute Env Tox, Cat 1

H401: Toxic to aquatic life; Acute Env Tox, Cat 2

H402: Harmful to aquatic life; Acute Env Tox, Cat 3

H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1

H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2

adoption according to regulation requirements.

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS: MSDS reformatted and Implementation of new GHS

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

\_\_\_\_\_

DGN: 7076272XKR (1029862)

\_\_\_\_\_