

Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 1 of 13

SAFETY DATA SHEET

SECTION 1

IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

As of the revision date above, this SDS meets the regulations in the United Kingdom excluding Northern Ireland.

1.1. PRODUCT IDENTIFIER

Product Name:MOBIL DYNAGEAR 2000Product Description:Base Oil and AdditivesProduct Code:2015A020R550

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST Intended Use: Grease

Uses advised against: This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above.

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Supplier:

SOL BARBADOS LIMITED Spring Garden Highway St. Michael BB12051 Barbados

Supplier General Contact:

1-246-233-0711, 1-246-467-4741

1.4. EMERGENCY TELEPHONE NUMBER 24 Hour Emergency Telephone: National Poison Control Centre:

+1 703-741-5970 (CHEMTREC) (UK) 111

SECTION 2

HAZARDS IDENTIFICATION

2.1. CLASSIFICATION OF SUBSTANCE OR MIXTURE

Classification according to GB CLP Skin Sensitiser: Category 1., H317: May cause allergic skin reaction. Chronic aquatic toxicant: Category 3., H412: Harmful to aquatic life with long lasting effects.

2.2. LABEL ELEMENTS

Label elements according to GB CLP

Pictograms:



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 2 of 13



Signal Word: Warning

Hazard Statements:

Health:

H317: May cause allergic skin reaction.

Environment:

H412: Harmful to aquatic life with long lasting effects.

Precautionary Statements:

Prevention:

P261: Avoid breathing fumes.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

Response:

P302 + P352: IF ON SKIN: Wash with plenty of soap and water.

P333 + P313: If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364: Take off contaminated clothing and wash it before reuse.

Disposal:

P501: Dispose of contents and container in accordance with local regulations.

Contains: 5,5'-DITHIOBIS-1.3,4--THIADIAZOLE-2(3H)-THIONE

2.3. OTHER HAZARDS

Physical / Chemical Hazards:

No significant hazards.

Health Hazards:

High-pressure injection under skin may cause serious damage. Mildly irritating to skin. May be irritating to the eyes, nose, throat, and lungs.

Environmental Hazards:

No additional hazards.Material does not meet the criteria for PBT or vPvB in accordance with REACH Annex XIII.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1. SUBSTANCES Not Applicable. This material is regulated as a mixture.



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 3 of 13

3.2. MIXTURES

This material is defined as a mixture.

Reportable hazardous substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

Name	CAS#	EC#	Registration#	Concentration	GHS/CLP classification
5,5'-DITHIOBIS-1.3,4THIADIAZOLE-2(3H)- THIONE	72676-55-2	276-763-0	01-2120119820-64	1 - < 5%	[Aquatic Acute 2 H401], Aquatic Chronic 2 H411, Skin Sens. 1B H317
AMINES, C12-14-TERT-ALKYL	-	701-175-2	01-2119456798-18	0.1 - < 0.25%	Acute Tox. 2 H330, Acute Tox. 3 H311, Acute Tox. 4 H302, Skin Sens. 1A H317, Aquatic Acute 1 H400 (M factor 1), Aquatic Chronic 1 H410 (M factor 1), Skin Corr. 1B H314
BUTENE, HOMOPOLYMER	9003-29-6	500-004-7	01-2119493067-32	10 - < 20%	Asp. Tox. 1 H304
C16-18-(EVEN NUMBERED, SATURATED AND UNSATURATED)-ALKYLAMINES	1213789-63-9	627-034-4	01-2119473797-19	0.01 - < 0.025%	Acute Tox. 4 H302, Asp. Tox. 1 H304, STOT SE 3 H335, Aquatic Acute 1 H400 (M factor 10), Aquatic Chronic 1 H410 (M factor 10), Skin Corr. 1B H314, STOT RE 2 H373
NAPHTHALENESULFONIC ACID, DINONYL-, BARIUM SALT (2:1)	1474044-80-8	939-718-2	01-2119980986-14	0.1 - < 1%	Acute Tox. 4 H302, Skin Irrit. 2 H315
GRAPHITE	7782-42-5	231-955-3	NE	1 - < 5%	OEL
MOLYBDENUM (IV) SULPHIDE	1317-33-5	215-263-9	EXEMPT	1 - < 5%	OEL
ZINC DIALKYL DITHIOPHOSPHATE	68457-79-4	270-608-0	01-2119493628-22	1 - < 2.5%	[Aquatic Acute 2 H401], Aquatic Chronic 2 H411, Skin Irrit. 2 H315, Eye Dam. 1 H318

Note - any classification in brackets is a GHS building block that was not adopted in GB CLP and therefore is not applicable in the countries which have implemented CLP and is shown for informational purposes only.

* All concentrations are percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Note: See SDS Section 16 for full text of hazard statements.

SECTION 4

FIRST AID MEASURES

4.1. DESCRIPTION OF FIRST AID MEASURES

INHALATION

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

SKIN CONTACT



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 4 of 13

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

First aid is normally not required. Seek medical attention if discomfort occurs.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Local necrosis as evidenced by delayed onset of pain and tissue damage a few hours after injection. Itching and rash from allergic skin reaction.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

The need to have special means for providing specific and immediate medical treatment available in the workplace is not expected.

SECTION 5

FIRE FIGHTING MEASURES

5.1. EXTINGUISHING MEDIA

Suitable Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO2) to extinguish flames.

Unsuitable Extinguishing Media: Straight streams of water

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous Combustion Products: Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulphur oxides

5.3. ADVICE FOR FIRE FIGHTERS

Fire Fighting Instructions: Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

FLAMMABILITY PROPERTIES

 Flash Point [Method]: >200°C (392°F) [EST. FOR OIL, ASTM D-92 (COC)]

 Upper/Lower Flammable Limits (Approximate volume % in air): UEL: No data available

 data available

 Autoignition Temperature: No data available

SECTION 6

ACCIDENTAL RELEASE MEASURES

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

NOTIFICATION PROCEDURES



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 5 of 13

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: respiratory protection will be necessary only in special cases, e.g., formation of mists. Half-face or full-face respirator with filter(s) for dust/organic vapor or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to hydrocarbons are recommended. Gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

6.2. ENVIRONMENTAL PRECAUTIONS

Prevent entry into waterways, sewers, basements or confined areas.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Land Spill: Scrape up spilled material with shovels into a suitable container for recycle or disposal.

Water Spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Skim from surface

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

6.4. REFERENCES TO OTHER SECTIONS

See Sections 8 and 13.

HANDLING AND STORAGE

7.1. PRECAUTIONS FOR SAFE HANDLING

Avoid contact with skin. Prevent small spills and leakage to avoid slip hazard.

Static Accumulator: This material is not a static accumulator.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

Do not store in open or unlabelled containers. Keep away from incompatible materials.

7.3. SPECIFIC END USES

SECTION 7

Section 1 informs about identified end-uses. No industrial or sector specific guidance available.



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 6 of 13

SECTION 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. CONTROL PARAMETERS

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit/Sta	indard	Note	Source
GRAPHITE	Inhalable dust.	TWA	10 mg/m3		UK EH40
GRAPHITE	Respirabl e dust.	TWA	4 mg/m3		UK EH40
GRAPHITE	Inhalable particles.	TWA	10 mg/m3		ACGIH
GRAPHITE	Respirabl e fraction.	TWA	2 mg/m3		ACGIH
MOLYBDENUM (IV) SULPHIDE [as Mo]		STEL	20 mg/m3		UK EH40
MOLYBDENUM (IV) SULPHIDE [as Mo]		TWA	10 mg/m3		UK EH40
MOLYBDENUM (IV) SULPHIDE [as Mo]	Inhalable fraction.	TWA	10 mg/m3		ACGIH
MOLYBDENUM (IV) SULPHIDE [as Mo]	Respirabl e fraction.	TWA	3 mg/m3		ACGIH
NAPHTHALENESULFONIC ACID, DINONYL-, BARIUM SALT (2:1) [as Ba]		TWA	0.5 mg/m3		UK EH40
NAPHTHALENESULFONIC ACID, DINONYL-, BARIUM SALT (2:1) [as Ba]		TWA	0.5 mg/m3		ACGIH

UK EH40 Workplace Exposure Limits. Exposure limits for use with Control of Substances Hazardous to Health Regulations 2002 (as amended)

Note: Information about recommended monitoring procedures can be obtained from the relevant agency(ies)/institute(s):

UK

Health and Safety Executive (HSE)

8.2. EXPOSURE CONTROLS

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions.



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 7 of 13

> Control measures to consider: No special requirements under ordinary conditions of use and with adequate ventilation.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No protection is ordinarily required under normal conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended.

Eye Protection: If contact is likely, safety glasses with side shields are recommended.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include: Chemical/oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9

PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Ex on Mobil

Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 8 of 13

> **Physical State:** Solid Form: Semi-fluid Colour: Dark Grav Characteristic Odour: Odour Threshold: No data available pH: Not technically feasible Melting Point: No data available Freezing Point: No data available Initial Boiling Point / and Boiling Range: > 316°C (600°F) [test method unavailable] >200°C (392°F) [EST. FOR OIL, ASTM D-92 (COC)] Flash Point [Method]: Evaporation Rate (n-butyl acetate = 1): No data available Flammability (Solid, Gas): Not technically feasible **Upper/Lower Flammable Limits (Approximate volume % in air):** UEL: No data available LEL: No data available Vapour Pressure: < 0.013 kPa (0.1 mm Hg) at 20 °C [test method unavailable] Vapour Density (Air = 1): No data available Relative Density (at 15 °C): 1 [test method unavailable] Solubility(ies): water Negligible Partition coefficient (n-Octanol/Water Partition Coefficient): > 3.5 [test method unavailable] Autoignition Temperature: No data available Decomposition Temperature: No data available 2000 cSt (2000 mm2/sec) at 40°C [Base oil] [test method unavailable] Viscosity: Explosive Properties: None **Oxidizing Properties:** None

9.2. OTHER INFORMATION

DMSO Extract (mineral oil only), IP-346: <3 %wt

NOTE: Most physical properties above are for the oil component in the material.

SECTION 10

STABILITY AND REACTIVITY

10.1. REACTIVITY: See sub-sections below.

10.2. CHEMICAL STABILITY: Material is stable under normal conditions.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

10.4. CONDITIONS TO AVOID: Excessive heat. High energy sources of ignition.

10.5. INCOMPATIBLE MATERIALS: Strong oxidisers

10.6. HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 9 of 13

Hazard Class	Conclusion / Remarks
Inhalation	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
Ingestion	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin Corrosion/Irritation: No end point data for material.	Mildly irritating to skin with prolonged exposure. Based on assessment of the components.
Eye	
Serious Eye Damage/Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.
Sensitisation	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: No end point data for material.	May cause allergic skin reaction. Based on assessment of the components.
Aspiration: Data available.	Not expected to be an aspiration hazard. Based on physico- chemical properties of the material.
Germ Cell Mutagenicity: No end point data for material.	Not expected to be a germ cell mutagen. Based on assessment of the components.
Carcinogenicity: No end point data for material.	Not expected to cause cancer. Based on assessment of the components.
Reproductive Toxicity: No end point data for material.	Not expected to be a reproductive toxicant. Based on assessment of the components.
Lactation: No end point data for material.	Not expected to cause harm to breast-fed children.
Specific Target Organ Toxicity (STOT)	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.

TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
	Dermal Lethality: LD 50 251 mg/kg (Rat); Inhalation Lethality: 4 hour(s) LC50 1.19 mg/l (Vapour) (Rat); Oral Lethality: LD 50 612 mg/kg (Rat)
NAPHTHALENESULFONIC ACID, DINONYL-, BARIUM SALT (2:1)	Oral Lethality: LD 50 1750 mg/kg (Rat)

OTHER INFORMATION

For the product itself:

An ingredient or ingredients that are classified as a skin sensitizer. **Contains:**

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 10 of 13

test, and/or other screening tests. Dermal and inhalation studies showed minimal effects; lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitising in test animals.

SECTION 12

ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

12.1. TOXICITY

Material -- Expected to be harmful to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

12.2. PERSISTENCE AND DEGRADABILITY

Biodegradation:

Base oil component -- Expected to be inherently biodegradable

12.3. BIOACCUMULATIVE POTENTIAL

Base oil component -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

12.4. MOBILITY IN SOIL

Base oil component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

12.5. PERSISTENCE, BIOACCUMULATION AND TOXICITY FOR SUBSTANCE(S)

Material does not meet the Reach Annex XIII criteria for PBT or vPvB.

12.6. OTHER ADVERSE EFFECTS

No adverse effects are expected.

SECTION 13

DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

13.1. WASTE TREATMENT METHODS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Suitable routes of disposal are supervised incineration, preferentially with energy recovery, or appropriate recycling methods in accordance with applicable regulations and material characteristics at the time of disposal.

European Waste Code: 12 01 12*

NOTE: These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code(s).

This material is considered as hazardous waste pursuant to The Hazardous Waste Regulations (HWR), and



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 11 of 13

subject to the provisions of those Regulations.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14 TRANSPORT INFORMATION

LAND (ADR/RID): 14.1-14.6 Not Regulated for Land Transport

INLAND WATERWAYS (ADN): 14.1-14.6 Not Regulated for Inland Waterways Transport

SEA (IMDG): 14.1-14.6 Not Regulated for Sea Transport according to IMDG-Code

SEA (MARPOL 73/78 Convention - Annex II):

- 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not classified according to Annex II
- AIR (IATA): 14.1-14.6 Not Regulated for Air Transport

SECTION 15 REGULATORY INFORMATION

REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

Listed or exempt from listing/notification on the following chemical inventories : AIIC, DSL, ENCS, IECSC, KECI, PICCS, TCSI, TSCA

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

Applicable UK legislation:

UK REACH [... Registration, Evaluation, Authorisation and Restriction of Chemicals ... and amendments thereto] GB CLP [Classification, labelling and packaging of substances and mixtures.. and amendments thereto]

REACH Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII):

The following entries of Annex XVII may be considered for this product: None



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 12 of 13

15.2. CHEMICAL SAFETY ASSESSMENT

REACH Information: A Chemical Safety Assessment has been carried out for one or more substances present in the material.

SECTION '	16
-----------	----

OTHER INFORMATION

REFERENCES: Sources of information used in preparing this SDS included one or more of the following: results from in house or supplier toxicology studies, CONCAWE Product Dossiers, publications from other trade associations, such as the EU Hydrocarbon Solvents REACH Consortium, U.S. HPV Program Robust Summaries, the EU IUCLID Data Base, U.S. NTP publications, and other sources, as appropriate.

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

Acronym	Full text
N/A	Not applicable
N/D	Not determined
NE	Not established
VOC	Volatile Organic Compound
AIIC	Australian Inventory of Industrial Chemicals
AIHA WEEL	American Industrial Hygiene Association Workplace Environmental Exposure Limits
ASTM	ASTM International, originally known as the American Society for Testing and Materials (ASTM)
DSL	Domestic Substance List (Canada)
EINECS	European Inventory of Existing Commercial Substances
ELINCS	European List of Notified Chemical Substances
ENCS	Existing and new Chemical Substances (Japanese inventory)
IECSC	Inventory of Existing Chemical Substances in China
KECI	Korean Existing Chemicals Inventory
NDSL	Non-Domestic Substances List (Canada)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances
TLV	Threshold Limit Value (American Conference of Governmental Industrial Hygienists)
TSCA	Toxic Substances Control Act (U.S. inventory)
UVCB	Substances of Unknown or Variable composition, Complex reaction products or Biological materials
LC	Lethal Concentration
LD	Lethal Dose
LL	Lethal Loading
EC	Effective Concentration
EL	Effective Loading
NOEC	No Observable Effect Concentration
NOELR	No Observable Effect Loading Rate

Classification according to GB CLP

Classification according to GB CLP	Classification procedure
Aquatic Chronic 3; H412	Calculation
Skin Sens. 1; H317	Calculation

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):



Product Name: MOBIL DYNAGEAR 2000 Revision Date: 23 Aug 2022 Revision Number: 1.00 Page 13 of 13

Acute Tox. 4 H302: Harmful if swallowed; Acute Tox Oral, Cat 4 Asp. Tox. 1 H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1 Acute Tox. 3 H311: Toxic in contact with skin; Acute Tox Dermal, Cat 3 Skin Corr. 1B H314: Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1B Skin Irrit. 2 H315: Causes skin irritation; Skin Corr/Irritation, Cat 2 Skin Sens. 1 H317: May cause allergic skin reaction; Skin Sensitization, Cat 1 Eye Dam. 1 H318: Causes serious eye damage; Serious Eye Damage/Irr, Cat 1 Acute Tox. 2 H330: Fatal if inhaled; Acute Tox Inh, Cat 2 STOT SE 3 H335: May cause respiratory irritation; Target Organ Single, Resp Irr STOT RE 2 H373: May cause damage to organs through prolonged or repeated exposure; Target Organ, Repeated, Cat 2 Aquatic Acute 1 H400: Very toxic to aquatic life; Acute Env Tox, Cat 1 [Aquatic Acute 2 H401]: Toxic to aquatic life; Acute Env Tox, Cat 2 Aquatic Chronic 1 H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1 Aquatic Chronic 2 H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

No revision information

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

Internal Use Only MHC: 0B, 0B, 0, 0, 2, 0 PPEC: C

DGN: 7116159XBB (1008826)

ANNEX

Annex not required for this material.