

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 1 of 16

SAFETY DATA SHEET

SECTION 1	IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING
------------------	---

As of the revision date above, this SDS meets the regulations in the United Kingdom excluding Northern Ireland.

1.1. PRODUCT IDENTIFIER

Product Name: WYROL 6
Product Description: Hydrocarbons and Additives
Product Code: 201570204535, 407392, 661827-60

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST

Intended Use: Metal processing fluid additive

Identified Uses:

Use of lubricants in high energy open processes - Industrial
Use of lubricants in high energy open processes - Professional

Uses advised against: This product is not recommended for any industrial, professional or consumer use other than the Identified Uses above.

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET

Supplier: ExxonMobil Petroleum & Chemical BV
POLDERDIJKWEG
B-2030 Antwerpen
Belgium

Product Technical Information:	(UK) 0800 028 2851
Supplier General Contact:	(UK) 0800 028 2851
SDS Internet Address:	www.msds.exxonmobil.com
E-Mail:	sds.uk@exxonmobil.com
Supplier / Registrant:	(BE) +32 3 790 3111

1.4. EMERGENCY TELEPHONE NUMBER

24 Hour Emergency Telephone:	(UK) (+44) 870 8200418
National Poison Control Centre:	(UK) 111

SECTION 2	HAZARDS IDENTIFICATION
------------------	-------------------------------

2.1. CLASSIFICATION OF SUBSTANCE OR MIXTURE

Classification according to CLP

Aspiration toxicant: Category 1., H304: May be fatal if swallowed and enters airways.
Acute aquatic toxicant: Category 1., H400: Very toxic to aquatic life.
Chronic aquatic toxicant: Category 2., H411: Toxic to aquatic life with long lasting effects.

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 2 of 16

2.2. LABEL ELEMENTS

Label elements according to CLP

Pictograms:



Signal Word: Danger

Hazard Statements:

Health:

H304: May be fatal if swallowed and enters airways.

Environment:

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

Supplemental:

EUH066: Repeated exposure may cause skin dryness or cracking.

Precautionary Statements:

Prevention:

P273: Avoid release to the environment.

Response:

P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P331: Do NOT induce vomiting.

P391: Collect spillage.

Storage:

P405: Store locked up.

Disposal:

P501: Dispose of contents and container in accordance with local regulations.

Contains: Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics

2.3. OTHER HAZARDS

Physical / Chemical Hazards:

Material can accumulate static charges which may cause an ignition. Material can release vapours that readily form flammable mixtures. Vapour accumulation could flash and/or explode if ignited. Combustible.

Health Hazards:

Repeated exposure may cause skin dryness or cracking. May be irritating to the skin, nose, throat, and lungs.

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 3 of 16

Environmental Hazards:

No additional hazards. Material does not meet the criteria for PBT or vPvB in accordance with REACH Annex XIII.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

3.1. SUBSTANCES Not Applicable. This material is regulated as a mixture.

3.2. MIXTURES

This material is defined as a mixture.

Reportable hazardous substance(s) complying with the classification criteria and/or with an exposure limit (OEL)

Name	CAS#	EC#	Registration#	Concentration *	GHS/CLP classification
2,6-DI-TERT-BUTYL-P-CRESOL	128-37-0	204-881-4	01-2119565113-46	0.1 - < 1%	Aquatic Acute 1 H400 (M factor 1), Aquatic Chronic 1 H410 (M factor 1)
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics		926-141-6	01-2119456620-43	10 - < 20%	[Flam. Liq. 4 H227], Asp. Tox. 1 H304, EUH066
DODECANOIC ACID, METHYL ESTER	111-82-0	203-911-3	01-2119487989-06	80 - < 90%	Aquatic Acute 1 H400 (M factor 1), Aquatic Chronic 2 H411

Note - any classification in brackets is a GHS building block that was not adopted in CLP and therefore is not applicable in the countries which have implemented CLP and is shown for informational purposes only.

Note: Any entry in the EC# column that begins with the number "9" is a Provisional List Number provided by ECHA pending publication of the official EC Inventory Number for the substance. See Section 15 for additional CAS number information for the substance.

Note: See SDS Section 16 for full text of hazard statements.

SECTION 4 FIRST AID MEASURES

4.1. DESCRIPTION OF FIRST AID MEASURES

INHALATION

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

SKIN CONTACT

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse.

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 4 of 16

EYE CONTACT

Flush thoroughly with water. If irritation occurs, get medical assistance.

INGESTION

Seek immediate medical attention. Do not induce vomiting.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

Redness, dry cracking of skin.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

SECTION 5	FIRE FIGHTING MEASURES
------------------	-------------------------------

5.1. EXTINGUISHING MEDIA

Suitable Extinguishing Media: Use water fog, foam, dry chemical or carbon dioxide (CO₂) to extinguish flames.

Unsuitable Extinguishing Media: Straight streams of water

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE

Hazardous Combustion Products: Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulphur oxides

5.3. ADVICE FOR FIRE FIGHTERS

Fire Fighting Instructions: Evacuate area. Prevent run-off from fire control or dilution from entering streams, sewers or drinking water supply. Fire-fighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

Unusual Fire Hazards: Combustible. Pressurised mists may form a flammable mixture.

FLAMMABILITY PROPERTIES

Flash Point [Method]: >70°C (158°F) [ASTM D-93]

Upper/Lower Flammable Limits (Approximate volume % in air): UEL: No data available LEL: No data available

Autoignition Temperature: No data available

SECTION 6	ACCIDENTAL RELEASE MEASURES
------------------	------------------------------------

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES

NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

PROTECTIVE MEASURES

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if

Product Name: WYROL 6

Revision Date: 10 Mar 2021

Revision Number: 2.00

Page 5 of 16

required, due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

For emergency responders: Respiratory protection: half-face or full-face respirator with filter(s) for organic vapor and, when applicable, H₂S, or Self Contained Breathing Apparatus (SCBA) can be used depending on the size of spill and potential level of exposure. If the exposure cannot be completely characterized or an oxygen deficient atmosphere is possible or anticipated, SCBA is recommended. Work gloves that are resistant to aromatic hydrocarbons are recommended. Note: gloves made of polyvinyl acetate (PVA) are not water-resistant and are not suitable for emergency use. Chemical goggles are recommended if splashes or contact with eyes is possible. Small spills: normal antistatic work clothes are usually adequate. Large spills: full body suit of chemical resistant, antistatic material is recommended.

6.2. ENVIRONMENTAL PRECAUTIONS

Large Spills: Dyke far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP

Land Spill: Stop leak if you can do so without risk. Do not touch or walk through spilled material. Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.

Water Spill: Stop leak if you can do so without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

6.4. REFERENCES TO OTHER SECTIONS

See Sections 8 and 13.

SECTION 7

HANDLING AND STORAGE

7.1. PRECAUTIONS FOR SAFE HANDLING

Avoid breathing mists or vapour. Avoid contact with skin. Small metal particles from machining may cause abrasion of the skin and may predispose to dermatitis. Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or earthing procedures. However, bonding and earthing may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics - Code of practice for the avoidance of hazards due to static electricity).

Static Accumulator: This material is a static accumulator.

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 6 of 16

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES

The type of container used to store the material may affect static accumulation and dissipation. Keep container closed. Handle containers with care. Open slowly in order to control possible pressure release. Store in a cool, well-ventilated area. Storage containers should be earthed and bonded. Fixed storage containers, transfer containers and associated equipment should be earthed and bonded to prevent accumulation of static charge.

7.3. SPECIFIC END USES

Section 1 informs about identified end-uses. No industrial or sector specific guidance available.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1. CONTROL PARAMETERS

EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit/Standard			Note	Source
2,6-DI-TERT-BUTYL-P-CRESOL		TWA	10 mg/m ³			UK EH40
2,6-DI-TERT-BUTYL-P-CRESOL	Inhalable fraction and vapour	TWA	2 mg/m ³			ACGIH
HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS	Vapour.	RCP - TWA	1200 mg/m ³	164 ppm	Total Hydrocarbons	ExxonMobil

UK EH40 Workplace Exposure Limits. Exposure limits for use with Control of Substances Hazardous to Health Regulations 2002 (as amended)

Note: Information about recommended monitoring procedures can be obtained from the relevant agency(ies)/institute(s):

UK Health and Safety Executive (HSE)

DERIVED NO EFFECT LEVEL (DNEL)/DERIVED MINIMAL EFFECT LEVEL (DMEL)

Worker

Substance Name	Dermal	Inhalation
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	NA	NA

Consumer

Substance Name	Dermal	Inhalation	Oral
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	NA	NA	NA

Note: The Derived No Effect Level (DNEL) is an estimated safe level of exposure that is derived from toxicity data in

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 7 of 16

accord with specific guidance within the REACH regulation. The DNEL may differ from an Occupational Exposure Limit (OEL) for the same chemical. OELs may be recommended by an individual company, a governmental regulatory body or an expert organization, such as the Scientific Committee for Occupational Exposure Limits (SCOEL) or the American Conference of Governmental Industrial Hygienists (ACGIH). OELs are considered to be safe exposure levels for a typical worker in an occupational setting for an 8-hour work shift, 40 hour work week, as a time weighted average (TWA) or a 15 minute short-term exposure limit (STEL). While also considered to be protective of health, OELs are derived by a process different from that of REACH.

PREDICTED NO EFFECT CONCENTRATION (PNEC)

Substance Name	Aqua (fresh water)	Aqua (marine water)	Aqua (intermittent release)	Sewage treatment plant	Sediment	Soil	Oral (secondary poisoning)
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	NA	NA	NA	NA	NA	NA	NA

8.2. EXPOSURE CONTROLS

ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

Use explosion-proof ventilation equipment to stay below exposure limits.

PERSONAL PROTECTION

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

Respiratory Protection: If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

Half-face filter respirator Type AP filter material., European Committee for Standardization (CEN) standards EN 136, 140 and 405 provide respirator masks and EN 149 and 143 provide filter recommendations.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapour warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

Hand Protection: Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

If prolonged or repeated contact is likely, chemical-resistant gloves are recommended. If contact with

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 8 of 16

forearms is likely, wear gauntlet-style gloves. Nitrile, minimum 0.38 mm thickness or comparable protective barrier material with a high performance level for continuous contact use conditions, permeation breakthrough minimum 480 minutes in accordance with CEN standards EN 420 and EN 374.

Eye Protection: If contact is likely, safety glasses with side shields are recommended. Chemical type goggles should be worn during misting operations.

Skin and Body Protection: Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:
If prolonged or repeated contact is likely, chemical, and oil resistant clothing is recommended.

Specific Hygiene Measures: Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Note: Physical and chemical properties are provided for safety, health and environmental considerations only and may not fully represent product specifications. Contact the Supplier for additional information.

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid
Colour: Colourless
Odour: Characteristic
Odour Threshold: No data available
pH: No data available
Melting Point: Not technically feasible
Freezing Point: No data available
Initial Boiling Point / and Boiling Range: 195°C (383°F) - 275°C (527°F) [ASTM D86]
Flash Point [Method]: >70°C (158°F) [ASTM D-93]
Evaporation Rate (n-butyl acetate = 1): No data available
Flammability (Solid, Gas): Not technically feasible
Upper/Lower Flammable Limits (Approximate volume % in air): UEL: No data available LEL: No data available
Vapour Pressure: < 0.1 kPa (0.75 mm Hg) at 20 °C [Estimated]
Vapour Density (Air = 1): > 2 at 101 kPa [Estimated]
Relative Density (at 15 °C): 0.862 [ASTM D4052]
Solubility(ies): water Negligible
Partition coefficient (n-Octanol/Water Partition Coefficient): > 3.5 [Estimated]
Autoignition Temperature: No data available
Decomposition Temperature: No data available

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 9 of 16

Viscosity: 2.3 cSt (2.3 mm²/sec) at 40°C [test method unavailable]
Explosive Properties: None
Oxidizing Properties: None

9.2. OTHER INFORMATION

Pour Point: 0°C (32°F) [ASTM D97]

SECTION 10 STABILITY AND REACTIVITY

10.1. REACTIVITY: See sub-sections below.

10.2. CHEMICAL STABILITY: Material is stable under normal conditions.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS: Hazardous polymerization will not occur.

10.4. CONDITIONS TO AVOID: Avoid heat, sparks, open flames and other ignition sources.

10.5. INCOMPATIBLE MATERIALS: Strong oxidisers

10.6. HAZARDOUS DECOMPOSITION PRODUCTS: Material does not decompose at ambient temperatures.

SECTION 11 TOXICOLOGICAL INFORMATION

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS

Hazard Class	Conclusion / Remarks
Inhalation	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Elevated temperatures or mechanical action may form vapours, mist, or fumes which may be irritating to the eyes, nose, throat, or lungs.
Ingestion	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin Corrosion/Irritation: No end point data for material.	May dry the skin leading to discomfort and dermatitis. Based on assessment of the components.
Eye	
Serious Eye Damage/Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.
Sensitisation	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: No end point data for material.	Not expected to be a skin sensitizer. Based on assessment of the components.
Aspiration: Data available.	May be fatal if swallowed and enters airways. Based on physico-

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 10 of 16

	chemical properties of the material.
Germ Cell Mutagenicity: No end point data for material.	Not expected to be a germ cell mutagen. Based on assessment of the components.
Carcinogenicity: No end point data for material.	Not expected to cause cancer. Based on assessment of the components.
Reproductive Toxicity: No end point data for material.	Not expected to be a reproductive toxicant. Based on assessment of the components.
Lactation: No end point data for material.	Not expected to cause harm to breast-fed children.
Specific Target Organ Toxicity (STOT)	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.

OTHER INFORMATION

For the product itself:

Vapour concentrations above recommended exposure levels are irritating to the eyes and the respiratory tract, may cause headaches and dizziness, are anaesthetic and may have other central nervous system effects. Prolonged and/or repeated skin contact with low viscosity materials may defat the skin resulting in possible irritation and dermatitis. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

SECTION 12 ECOLOGICAL INFORMATION

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

12.1. TOXICITY

Material -- Expected to be very toxic to aquatic organisms. May cause long-term adverse effects in the aquatic environment.

12.2. PERSISTENCE AND DEGRADABILITY

Biodegradation:

Majority of components -- Expected to be readily biodegradable.

Atmospheric Oxidation:

Hydrocarbon component -- Expected to degrade rapidly in air

12.3. BIOACCUMULATIVE POTENTIAL

Hydrocarbon component -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

12.4. MOBILITY IN SOIL

Hydrocarbon component -- Highly volatile, will partition rapidly to air. Not expected to partition to sediment and wastewater solids.

A component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

12.5. PERSISTENCE, BIOACCUMULATION AND TOXICITY FOR SUBSTANCE(S)

Material does not meet the Reach Annex XIII criteria for PBT or vPvB.

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 11 of 16

12.6. OTHER ADVERSE EFFECTS

No adverse effects are expected.

SECTION 13

DISPOSAL CONSIDERATIONS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

13.1. WASTE TREATMENT METHODS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

European Waste Code: 12 01 07*

NOTE: These codes are assigned based upon the most common uses for this material and may not reflect contaminants resulting from actual use. Waste producers need to assess the actual process used when generating the waste and its contaminants in order to assign the proper waste disposal code(s).

This material is considered as hazardous waste pursuant to The Hazardous Waste Regulations (HWR), and subject to the provisions of those Regulations.

Empty Container Warning Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

SECTION 14

TRANSPORT INFORMATION

LAND (ADR/RID)

14.1. UN Number: 3082

14.2. UN Proper Shipping Name (Technical Name): ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Methyl Laurate)

14.3. Transport Hazard Class(es): 9

14.4. Packing Group: III

14.5. Environmental Hazards: Yes

14.6. Special Precautions for users:

Classification Code: M6

Label(s) / Mark(s): 9, EHS

Hazard ID Number: 90

Hazchem EAC: 3Z

INLAND WATERWAYS (ADN)

14.1. UN (or ID) Number: 3082

Product Name: WYROL 6
 Revision Date: 10 Mar 2021
 Revision Number: 2.00
 Page 12 of 16

14.2. UN Proper Shipping Name (Technical Name): ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Methyl Laurate)
14.3. Transport Hazard Class(es): 9
14.4. Packing Group: III
14.5. Environmental Hazards: Yes
14.6. Special Precautions for users:
Hazard ID Number: 90
Label(s) / Mark(s): 9, EHS

SEA (IMDG)

14.1. UN Number: 3082
14.2. UN Proper Shipping Name (Technical Name): ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Methyl Laurate)
14.3. Transport Hazard Class(es): 9
14.4. Packing Group: III
14.5. Environmental Hazards: Marine Pollutant
14.6. Special Precautions for users:
Label(s): 9
EMS Number: F-A, S-F
Transport Document Name: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Methyl Laurate), 9, PG III, MARINE POLLUTANT

Footnote: Not subject to the provisions of UN3082 Environmentally hazardous substances liquid, n.o.s., if shipped in quantities of 5 liters or less per single or inner combination packaging as per IMDG code 2.10.2.7.

SEA (MARPOL 73/78 Convention - Annex II):

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
 Not classified according to Annex II

AIR (IATA)

14.1. UN Number: 3082
14.2. UN Proper Shipping Name (Technical Name): ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Methyl Laurate)
14.3. Transport Hazard Class(es): 9
14.4. Packing Group: III
14.5. Environmental Hazards: Yes
14.6. Special Precautions for users:
Label(s) / Mark(s): 9, EHS
Transport Document Name: UN3082, ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Methyl Laurate), 9, PG III

[Footnote: Not subject to the provisions of UN3082 Environmentally hazardous substances liquid, n.o.s., if shipped in quantities of 5 liters or less per single or inner combination packaging as per Special Provision A197.]

SECTION 15

REGULATORY INFORMATION

REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS

Product Name: WYROL 6
Revision Date: 10 Mar 2021
Revision Number: 2.00
Page 13 of 16

Listed or exempt from listing/notification on the following chemical inventories (May contain substance(s) subject to notification to the EPA Active TSCA inventory prior to import to USA): AIIIC, DSL, ENCS, IECSC, ISHL, KECI, PICCS, TCSI, TSCA

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR THE SUBSTANCE OR MIXTURE

Applicable UK legislation:

REACH [... Registration, Evaluation, Authorisation and Restriction of Chemicals ... and amendments thereto]
Health and Safety at Work etc. Act. [...limitation of emissions of volatile organic compounds...]
The Control of Major Accident Hazards (COMAH) Regulations. Product contains a substance that falls within the criteria. Refer to legislation for details of requirements taking into account the volume of product stored on site.
The Control of Substances Hazardous to Health (COSHH) Regulations [...protection of workers from the risks of chemical agents at work...]. Refer to legislation for details of requirements.
CLP [Classification, labelling and packaging of substances and mixtures.. and amendments thereto]

REACH Restrictions on the manufacturing, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII):

The following entries of Annex XVII may be considered for this product: None

15.2. CHEMICAL SAFETY ASSESSMENT

REACH Information: A Chemical Safety Assessment has been carried out for one or more substances present in the material.

SECTION 16	OTHER INFORMATION
------------	-------------------

REFERENCES: Sources of information used in preparing this SDS included one or more of the following: results from in house or supplier toxicology studies, CONCAWE Product Dossiers, publications from other trade associations, such as the EU Hydrocarbon Solvents REACH Consortium, U.S. HPV Program Robust Summaries, the EU IUCLID Data Base, U.S. NTP publications, and other sources, as appropriate.

List of abbreviations and acronyms that could be (but not necessarily are) used in this safety data sheet:

Acronym	Full text
N/A	Not applicable
N/D	Not determined
NE	Not established
VOC	Volatile Organic Compound
AIIIC	Australian Inventory of Industrial Chemicals
AIHA WEEL	American Industrial Hygiene Association Workplace Environmental Exposure Limits
ASTM	ASTM International, originally known as the American Society for Testing and Materials (ASTM)
DSL	Domestic Substance List (Canada)

Product Name: WYROL 6

Revision Date: 10 Mar 2021

Revision Number: 2.00

Page 14 of 16

EINECS	European Inventory of Existing Commercial Substances
ELINCS	European List of Notified Chemical Substances
ENCS	Existing and new Chemical Substances (Japanese inventory)
IECSC	Inventory of Existing Chemical Substances in China
KECI	Korean Existing Chemicals Inventory
NDSL	Non-Domestic Substances List (Canada)
NZIoC	New Zealand Inventory of Chemicals
PICCS	Philippine Inventory of Chemicals and Chemical Substances
TLV	Threshold Limit Value (American Conference of Governmental Industrial Hygienists)
TSCA	Toxic Substances Control Act (U.S. inventory)
UVCB	Substances of Unknown or Variable composition, Complex reaction products or Biological materials
LC	Lethal Concentration
LD	Lethal Dose
LL	Lethal Loading
EC	Effective Concentration
EL	Effective Loading
NOEC	No Observable Effect Concentration
NOELR	No Observable Effect Loading Rate

Classification according to CLP

Classification according to CLP	Classification procedure
Aquatic Acute 1; H400	Calculation
Aquatic Chronic 2; H411	Calculation
Asp. Tox. 1; H304	Based on test data

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

[Flam. Liq. 4 H227]: Combustible liquid; Flammable Liquid, Cat 4

Asp. Tox. 1 H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1

Aquatic Acute 1 H400: Very toxic to aquatic life; Acute Env Tox, Cat 1

Aquatic Chronic 1 H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1

Aquatic Chronic 2 H411: Toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 2

EUH066: Repeated exposure may cause skin dryness or cracking.

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

CLP Classification information was added.

CLP Classification information was modified.

Composition: Component Table for REACH information was modified.

Composition: Concentration Footnote information was deleted.

dnel table notes information was modified.

GHS CLP Supplemental Statements information was added.

GHS CLP Supplemental Statements information was deleted.

GHS Environmental Classification information was deleted.

GHS Environmental Hazards information was added.

GHS Environmental Hazards information was deleted.

GHS Environmental Hazards information was modified.

GHS Environmental Symbol information was deleted.

GHS Health Classification information was deleted.

GHS Health Hazards information was added.

GHS Health Hazards information was deleted.

GHS Health Symbol information was deleted.

Product Name: WYROL 6

Revision Date: 10 Mar 2021

Revision Number: 2.00

Page 15 of 16

GHS Precautionary Statements - Disposal information was added.
GHS Precautionary Statements - Disposal information was deleted.
GHS Precautionary Statements - Prevention information was added.
GHS Precautionary Statements - Prevention information was deleted.
GHS Precautionary Statements - Response information was added.
GHS Precautionary Statements - Response information was deleted.
GHS Precautionary Statements - Storage information was added.
GHS Precautionary Statements - Storage information was deleted.
GHS Signal Word information was added.
GHS Signal Word information was deleted.
GHS Symbol information was added.
GHS Target Organ Phrase information was deleted.
Hazard Identification: Section 3 Footnotes for CLP tables information was modified.
Section 01: Company Contact Methods information was modified.
Section 01: Company Emergency Contact information was modified.
Section 01: Company Mailing Address information was modified.
Section 08: Exposure Limits Table information was modified.
Section 08: Legal Basis information was added.
Section 08: PNEC notes information was deleted.
Section 09: Boiling Point °C(°F) information was modified.
Section 09: Pour Point °C(°F) information was modified.
Section 09: Relative Density information was modified.
Section 13: European Waste Code Hazardous Note information was modified.
Section 14: IATA Footnote information was added.
Section 14: IMDG Footnote information was added.
Section 15: EU Directives and Regulations information was modified.
Section 15: National Chemical Inventory Listing information was modified.
Section 15: REACH Annex XVII data information was added.
Section 16: Classification CLP/GHS Table information was modified.
Section 16: HCode Key information was modified.

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

Internal Use Only

MHC: 1A, 0, 0, 0, 1, 1

PPEC: C

DGN: 2026629XGB (555353)

Product Name: WYROL 6

Revision Date: 10 Mar 2021

Revision Number: 2.00

Page 16 of 16

ANNEX

Annex not required for this material.