

Product Name: MOBIL SHC GREASE 460 WT  
Revision Date: 20 May 2022  
Page 1 of 12

## SAFETY DATA SHEET

SECTION 1	PRODUCT AND COMPANY IDENTIFICATION
-----------	------------------------------------

### PRODUCT

Product Name: MOBIL SHC GREASE 460 WT  
Product Description: Synthetic Base Stocks and Additives  
Product Code: 2015A0209710, 643932-00  
Recommended Use: Grease

### COMPANY IDENTIFICATION

Supplier: EMG Lubricants GodoKaisha  
1-8-15, Kohnan, Minato-ku  
Tokyo 〒 108-8005 Japan

Supplier General Contact

0120-016-313

SECTION 2	HAZARDS IDENTIFICATION
-----------	------------------------

This material is not hazardous according to regulatory guidelines (see (M)SDS Section 15).

**Contains:** 5-NONYL-SALICYLALDOXIME, ALKENYL SUCCINIC ANHYDRIDE May produce an allergic reaction.

**Other hazard information:**

### PHYSICAL / CHEMICAL HAZARDS

No significant hazards.

### HEALTH HAZARDS

High-pressure injection under skin may cause serious damage. Excessive exposure may result in eye, skin, or respiratory irritation.

### ENVIRONMENTAL HAZARDS

No significant hazards.

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks

Product Name: MOBIL SHC GREASE 460 WT  
Revision Date: 20 May 2022  
Page 2 of 12

which may vary from person to person.

<b>SECTION 3</b>	<b>COMPOSITION / INFORMATION ON INGREDIENTS</b>
------------------	---

**Chemical Substance or Mixture Identification**

This material is defined as a mixture.

**Hazardous Substance(s) or Complex Substance(s) required for disclosure**

Name	CAS#	Concentration*	GHS Hazard Codes
5-NONYL-SALICYLALDOXIME	174333-80-3	0.1 - < 0.3%	H315, H318, H317, H360 (1B) (D), H360 (1B) (F), H400 (M factor 10), H410 (M factor 10)
ALKENYL SUCCINIC ANHYDRIDE	19780-11-1	0.1 - < 1%	H315, H319 (2A), H317
HEXANEDIOIC ACID, DILITHIUM SALT	18621-94-8	1 - < 5%	H302, H402
LITHIUM HYDROXIDE MONOHYDRATE	1310-66-3	0.1 - < 1%	H302, H314 (1B)

\* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by volume.

<b>SECTION 4</b>	<b>FIRST AID MEASURES</b>
------------------	---------------------------

**INHALATION**

Under normal conditions of intended use, this material is not expected to be an inhalation hazard.

**SKIN CONTACT**

Wash contact areas with soap and water. Remove contaminated clothing. Launder contaminated clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

**EYE CONTACT**

Flush thoroughly with water. If irritation occurs, get medical assistance.

**INGESTION**

First aid is normally not required. Seek medical attention if discomfort occurs.

**NOTE TO PHYSICIAN**

None

<b>SECTION 5</b>	<b>FIRE FIGHTING MEASURES</b>
------------------	-------------------------------

**EXTINGUISHING MEDIA**

Product Name: MOBIL SHC GREASE 460 WT  
Revision Date: 20 May 2022  
Page 3 of 12

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight Streams of Water

## FIRE FIGHTING

**Fire Fighting Instructions:** Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulfur oxides

## FLAMMABILITY PROPERTIES

**Flash Point [Method]:** >204° C (400° F) [ EST. FOR OIL, ASTM D-92 (COC)]

**Flammable Limits (Approximate volume % in air):** LEL: N/D UEL: N/D

**Autoignition Temperature:** N/D

## SECTION 6

## ACCIDENTAL RELEASE MEASURES

## NOTIFICATION PROCEDURES

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

## PERSONAL PRECAUTIONS

Avoid contact with spilled material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

## SPILL MANAGEMENT

**Land Spill:** Scrape up spilled material with shovels into a suitable container for recycle or disposal.

**Water Spill:** Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Skim from surface.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken.

Product Name: MOBIL SHC GREASE 460 WT

Revision Date: 20 May 2022

Page 4 of 12

For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

## ENVIRONMENTAL PRECAUTIONS

Prevent entry into waterways, sewers, basements or confined areas.

## SECTION 7 HANDLING AND STORAGE

### HANDLING (Technical Measures; Safety Handling Precautions; Contact Avoidance)

Avoid all personal contact. Prevent small spills and leakage to avoid slip hazard.

**Static Accumulator:** This material is not a static accumulator.

### STORAGE (Safe Storage Conditions; Safe Containers and Packaging Materials)

Do not store in open or unlabelled containers.

## SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### EXPOSURE LIMIT VALUES

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit / Standard			NOTE	Source
LITHIUM HYDROXIDE MONOHYDRATE		TWA	1 mg/m <sup>3</sup>			Japan OELs – JSOH
LITHIUM HYDROXIDE MONOHYDRATE		Ceiling	1 mg/m <sup>3</sup>			OARS WEEL

### Biological limits

No biological limits allocated.

NOTE: Limits/standards shown for guidance only. Follow applicable regulations.

### ENGINEERING CONTROLS

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

### PERSONAL PROTECTION

Product Name: MOBIL SHC GREASE 460 WT

Revision Date: 20 May 2022

Page 5 of 12

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include:

No protection is ordinarily required under normal conditions of use and with adequate ventilation.

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include:

Chemical resistant gloves are recommended. Nitrile, Viton

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include:

Chemical/oil resistant clothing is recommended.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## ENVIRONMENTAL CONTROLS

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

## SECTION 9

## PHYSICAL AND CHEMICAL PROPERTIES

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations

Product Name: MOBIL SHC GREASE 460 WT  
Revision Date: 20 May 2022  
Page 6 of 12

only and may not fully represent product specifications. Contact the Supplier for additional information.

#### BASIC PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Solid  
Color: Red  
Odor: Characteristic  
Melting Point: N/D  
Freezing Point: N/D  
Initial Boiling Point / Range: > 316° C (600° F) [Estimated]  
Flammability: Ignitable  
Lower and Upper Explosion Limit/Flammability Limit: Lower: N/D Upper: N/D  
Flash Point [Method]: >204° C (400° F) [ EST. FOR OIL, ASTM D-92 (COC)]  
Autoignition Temperature: N/D  
Decomposition Temperature: N/D  
pH: N/A  
Kinematic Viscosity: 460 cSt (460 mm<sup>2</sup>/sec) at 40 ° C | >16 cSt (16 mm<sup>2</sup>/sec) at 100° C  
Solubility in Water: Negligible  
Partition Coefficient: n-Octanol/water (log value): N/A  
Vapor Pressure: < 0.013 kPa (0.1 mm Hg) at 20 ° C [Estimated]  
Relative Density (at 15 ° C): 0.9  
Relative Vapor Density (Air = 1): N/D  
Particle Characteristics: Median Size: N/A Size Range: N/A

#### OTHER INFORMATION

Form: Semi-fluid  
Evaporation Rate (n-butyl acetate = 1): N/D  
Oxidizing Properties: See Hazards Identification Section.

NOTE: Most physical properties above are for the oil component in the material.

SECTION 10	STABILITY AND REACTIVITY
------------	--------------------------

**REACTIVITY:** See sub-sections below.

**STABILITY:** Material is stable under normal conditions.

**CONDITIONS TO AVOID:** Excessive heat. High energy sources of ignition.

**MATERIALS TO AVOID:** Strong oxidizers

Product Name: MOBIL SHC GREASE 460 WT  
Revision Date: 20 May 2022  
Page 7 of 12

**HAZARDOUS DECOMPOSITION PRODUCTS:** Material does not decompose at ambient temperatures.

**POSSIBILITY OF HAZARDOUS REACTIONS:** Hazardous polymerization will not occur.

<b>SECTION 11</b>	<b>TOXICOLOGICAL INFORMATION</b>
-------------------	----------------------------------

**INFORMATION ON TOXICOLOGICAL EFFECTS**

<b>Hazard Class</b>	<b>Conclusion / Remarks</b>
<b>Inhalation</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Irritation: No end point data for material.	Negligible hazard at ambient/normal handling temperatures.
<b>Ingestion</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
<b>Skin</b>	
Acute Toxicity: No end point data for material.	Minimally Toxic. Based on assessment of the components.
Skin Corrosion/Irritation: No end point data for material.	Negligible irritation to skin at ambient temperatures. Based on assessment of the components.
<b>Eye</b>	
Serious Eye Damage/Irritation: No end point data for material.	May cause mild, short-lasting discomfort to eyes. Based on assessment of the components.
<b>Sensitization</b>	
Respiratory Sensitization: No end point data for material.	Not expected to be a respiratory sensitizer.
Skin Sensitization: Data available.	Not expected to be a skin sensitizer. Based on test data for the material. Test(s) equivalent or similar to OECD Guideline 406 429
<b>Aspiration:</b> Data available.	Not expected to be an aspiration hazard. Based on physico-chemical properties of the material.
<b>Germ Cell Mutagenicity:</b> No end point data for material.	Not expected to be a germ cell mutagen. Based on assessment of the components.
<b>Carcinogenicity:</b> No end point data for material.	Not expected to cause cancer. Based on assessment of the components.
<b>Reproductive Toxicity:</b> No end point data for material.	Contains a substance that may be a reproductive toxicant. Based on assessment of the components.
<b>Lactation:</b> No end point data for material.	Not expected to cause harm to breast-fed children.
<b>Specific Target Organ Toxicity (STOT)</b>	
Single Exposure: No end point data for material.	Not expected to cause organ damage from a single exposure.
Repeated Exposure: No end point data for material.	Not expected to cause organ damage from prolonged or repeated exposure. Based on assessment of the components.

Product Name: MOBIL SHC GREASE 460 WT  
Revision Date: 20 May 2022  
Page 8 of 12

## TOXICITY FOR SUBSTANCES

NAME	ACUTE TOXICITY
HEXANEDIOIC ACID, DILITHIUM SALT	Oral Lethality: LD50 1098 mg/kg (Rat)

## OTHER INFORMATION

### For the product itself:

Component concentrations in this formulation would not be expected to cause skin sensitization, based on tests of the components, this formulation, or similar formulations.

### Contains:

Synthetic base oils: Not expected to cause significant health effects under conditions of normal use, based on laboratory studies with the same or similar materials. Not mutagenic or genotoxic. Not sensitizing in test animals and humans.

See Section 16 for a description of sources for reference data.

### IARC Classification:

The following ingredients are cited on the lists below: None.

### --REGULATORY LISTS SEARCHED--

1 = IARC 1

2 = IARC 2A

3 = IARC 2B

SECTION 12	ECOLOGICAL INFORMATION
------------	------------------------

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

### ECOTOXICITY

Material -- Not expected to be harmful to aquatic organisms.

### MOBILITY

Base oil component -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

**PERSISTENCE AND DEGRADABILITY** Not determined.

**BIOACCUMULATIVE POTENTIAL** Not determined.

### Hazard to the Ozone Layer

Not Applicable



Product Name: MOBIL SHC GREASE 460 WT  
Revision Date: 20 May 2022  
Page 9 of 12

## ECOLOGICAL DATA

### Ecotoxicity

Test	Duration	Organism Type	Test Results
Aquatic – Acute Toxicity	96 hour (s)	Brachydanio rerio	NOELR 103 mg/l: data for the material
Aquatic – Acute Toxicity	48 hour (s)	Ceriodaphnia dubia	EL50 105 mg/l: data for the material
Aquatic – Acute Toxicity	72 hour (s)	Pseudokirchneriella subcapitata	ErL50 105 mg/l: data for the material
Aquatic – Chronic Toxicity	28 day (s)	Brachydanio rerio	NOELR 1.2 mg/l: data for the material
Aquatic – Chronic Toxicity	6 day (s)	Ceriodaphnia dubia	NOELR 1.1 mg/l: data for the material
Aquatic – Chronic Toxicity	72 hour (s)	Pseudokirchneriella subcapitata	NOELR 105 mg/l: data for the material

See Section 16 for a description of sources for reference data.

<b>SECTION 13</b>	<b>DISPOSAL CONSIDERATIONS</b>
-------------------	--------------------------------

### Information on Safe and Environmentally Desirable Disposal or Recycling of Chemicals, Contaminated Containers and Packaging

#### DISPOSAL METHODS

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

#### DISPOSAL RECOMMENDATIONS

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

Product Name: MOBIL SHC GREASE 460 WT

Revision Date: 20 May 2022

Page 10 of 12

SECTION 14	TRANSPORT INFORMATION
------------	-----------------------

**LAND – Precautionary Transportation Measures & Conditions:**

Do not co-load together with dangerous substances categorized in Fire Cat. 1 and/or 6, and/or High Pressure Gases.

NOTE: Comply with applicable laws and regulations.

**SEA (IMDG):** Not Regulated for Sea Transport according to IMDG-Code

**Marine Pollutant:** No

**AIR (IATA):** Not Regulated for Air Transport

SECTION 15	REGULATORY INFORMATION
------------	------------------------

This material is not considered hazardous according to the Classification of Chemicals based on Globally Harmonized System of Classification and Labelling of Chemicals (GHS) (JIS Z 7252-2019).

**REGULATORY STATUS AND APPLICABLE LAWS AND REGULATIONS**

Listed or exempt from listing/notification on the following chemical inventories : IECSC, ISHL, TCSI, TSCA

**Special Cases:**

Inventory	Status
AIIC	Restrictions Apply
KECI	Restrictions Apply
NDSL	Restrictions Apply

**National Laws and Regulations:**

Fire Service Law: Not Dangerous Substances

ISHL: Notified Substances

ISHL: Labeling Substances

Maritime Pollution Prevention Law: Regulated

Poisonous and Deleterious Substances Control Law (PDSCL): Not Regulated

Product Name: MOBIL SHC GREASE 460 WT

Revision Date: 20 May 2022

Page 11 of 12

Pollutant Release and Transfer Register (PRTR): Not Regulated

Sewage Water Law: Mineral oil (5mg/l max.)

Waste Treatment Law : Controlled Industrial Waste

Water Pollution Control Law: Effluent Regulation (5mg/l max.)

**JAPANESE COMPOSITION INFORMATION****Industrial Safety and Health Law: Article 57, Chemical substances to be labelled:**

Name	Concentration
Mineral Oil	1-5 wt%

**Industrial Safety and Health Law: Article 57-2, Chemical substances to be notified:**

Name	ISHL Ordinance Number	Concentration
LITHIUM HYDROXIDE MONOHYDRATE	320	0.1-1 %weight

**Industrial Safety and Health Law: Article 57-2, Chemical Substances to be notified:**

Name	ISHL Ordinance Number	Concentration
Mineral Oil	168	1-5 %weight

ISHL Enforcement Order, Table 3-1, Manufacturing Permit Chemical Substances: None.

PRTR Class 1 Designated Chemical Substances: None.

PRTR Class 2 Designated Chemical Substances: None.

PDSCL Chemical Substances: None.

**SECTION 16 OTHER INFORMATION**

**SOURCE OF REFERENCE MATERIAL:** Sources of information used in preparing this SDS included one or more of the following: results from in house or supplier toxicology studies, CONCAWE Product Dossiers, publications from other trade associations, such as the EU Hydrocarbon Solvents REACH Consortium, U.S. HPV Program Robust Summaries, the EU IUCLID Data Base, U.S. NTP publications, and other sources, as appropriate.

**N/D = Not determined, N/A = Not applicable****KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):**

H302: Harmful if swallowed; Acute Tox Oral, Cat 4

H314(1B): Causes severe skin burns and eye damage; Skin Corr/Irritation, Cat 1B

H315: Causes skin irritation; Skin Corr/Irritation, Cat 2

H317: May cause allergic skin reaction; Skin Sensitization, Cat 1

H318: Causes serious eye damage; Serious Eye Damage/Irr, Cat 1

H319(2A): Causes serious eye irritation; Serious Eye Damage/Irr, Cat 2A

H360(1B) (D): May damage the unborn child; Repro Tox, Cat 1B (Develop)

H360(1B) (F): May damage fertility; Repro Tox, Cat 1B (Fertility)

Product Name: MOBIL SHC GREASE 460 WT

Revision Date: 20 May 2022

Page 12 of 12

---

H400: Very toxic to aquatic life; Acute Env Tox, Cat 1

H402: Harmful to aquatic life; Acute Env Tox, Cat 3

H410: Very toxic to aquatic life with long lasting effects; Chronic Env Tox, Cat 1

THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:

Composition: ISHL LABEL Table information was modified.

Composition: ISHL Table information was modified.

---

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, republication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

---

---

Internal Use Only

MHC: OB, OB, 0, 0, 0, 0

PPEC: C

DGN: 7082796XJP (1012605)

---