

Product Name: MOBILTHERM 603

Revision Date: 06 Jul 2021

Page 1 of 13

## MATERIAL SAFETY DATA SHEET

MSDS No.: AA00985-0000000011

**SECTION 1****PRODUCT AND COMPANY IDENTIFICATION****A. Product Name: MOBILTHERM 603****Product Description:** Severely Treated Base Oils**Product Code:** 201560802010, 680512**B. Recommended Use of Product and Restrictions in Use.****Recommended use of the product:** Heat transfer fluids**Restrictions in Use:** This product is not recommended for any industrial, professional or consumer use other than the identified uses above.**C. Manufacturer/Supplier information:****For details contact****Mobil Korea Lube Oil Inc.**

Level 22, Seoul Square bd., 416

Hangang-daero, Jung-gu,

Seoul Republic of Korea

Emergency Response Number	00-308-13-2549 / +1-703-527-3887
Supplier General Contact	82-2-750-8700
FAX	82-2-750-8751

**SECTION 2****HAZARDS IDENTIFICATION**

This material is hazardous according to regulatory guidelines (see (M)SDS Section 15).

**A. Hazard Classification:**

Aspiration toxicant: Category 1.

**B. Label Elements Including Precautionary Statements:****Hazard Pictogram:**

Product Name: MOBILTHERM 603  
Revision Date: 06 Jul 2021  
Page 2 of 13

**Signal Word:** Danger

**Hazard Statements:**

Health: H304: May be fatal if swallowed and enters airways.

**Precautionary Statements:**

Response: P301 + P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P331: Do NOT induce vomiting.

Storage: P405: Store locked up.

Disposal: P501: Dispose of contents and container in accordance with local regulations.

**C. Other Hazards Which Are Not Included In The Classification Criteria**

**Physical / Chemical Hazards**

No significant hazards.

**Health Hazards**

Excessive exposure may result in eye, skin, or respiratory irritation.

**Environmental Hazards**

No significant hazards.

<b>NFPA Hazard ID:</b>	Health: 1	Flammability: 1	Reactivity: 0
<b>HMIS Hazard ID:</b>	Health: 1	Flammability: 1	Reactivity: 0

**NOTE:** This material should not be used for any other purpose than the intended use in Section 1 without expert advice. Health studies have shown that chemical exposure may cause potential human health risks which may vary from person to person.

SECTION 3	COMPOSITION / INFORMATION ON INGREDIENTS
-----------	--

This material is defined as a complex substance.

**Hazardous Substance(s) or Complex Substance(s) required for disclosure**

Name	Other Name	CAS # or Id. No.	Concentration*	GHS Hazard Codes
SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	-	KE-12546	50 - < 60%	H304
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE	-	KE-12602	50 - < 60%	H304

\* All concentrations are percent by weight unless material is a gas. Gas concentrations are in percent by

Product Name: MOBILTHERM 603  
Revision Date: 06 Jul 2021  
Page 3 of 13

volume.

<b>SECTION 4</b>	<b>FIRST AID MEASURES</b>
------------------	---------------------------

**A. Eye Contact**

Flush thoroughly with water. If irritation occurs, get medical assistance.

**B. Skin Contact**

Wash contact areas with soap and water.

**C. Inhalation**

Remove from further exposure. For those providing assistance, avoid exposure to yourself or others. Use adequate respiratory protection. If respiratory irritation, dizziness, nausea, or unconsciousness occurs, seek immediate medical assistance. If breathing has stopped, assist ventilation with a mechanical device or use mouth-to-mouth resuscitation.

**D. Ingestion**

Seek immediate medical attention. Do not induce vomiting.

**E. Other note to physician**

If ingested, material may be aspirated into the lungs and cause chemical pneumonitis. Treat appropriately.

**Acute and Delayed Symptoms/Effects**

See Toxicological Section

**Pre-existing Medical Conditions Which May Be Aggravated By Exposure**

None.

<b>SECTION 5</b>	<b>FIRE FIGHTING MEASURES</b>
------------------	-------------------------------

**Flammability Properties**

Flash Point [Method]: >200° C (392° F)

Autoignition Temperature: N/D

Flammable Limits (Approximate volume % in air): LEL: 0.9 UEL: 7.0

**A. Suitable (and Unsuitable) Extinguishing Media**

**Appropriate Extinguishing Media:** Use water fog, foam, dry chemical or carbon dioxide (CO<sub>2</sub>) to extinguish flames.

**Inappropriate Extinguishing Media:** Straight Streams of Water

**B. Specific Hazards arising from the Chemical**

**Unusual Fire Hazards:** None

**Hazardous Combustion Products:** Aldehydes, Incomplete combustion products, Oxides of carbon, Smoke, Fume, Sulfur oxides

#### C. Special Protective Equipment and Precautions for Fire-fighters

Evacuate area. Prevent runoff from fire control or dilution from entering streams, sewers, or drinking water supply. Firefighters should use standard protective equipment and in enclosed spaces, self-contained breathing apparatus (SCBA). Use water spray to cool fire exposed surfaces and to protect personnel.

<b>SECTION 6</b>	<b>ACCIDENTAL RELEASE MEASURES</b>
------------------	------------------------------------

#### A. Personal Precautions and Protective Equipment

Avoid contact with spilled material. Warn or evacuate occupants in surrounding and downwind areas if required due to toxicity or flammability of the material. See Section 5 for fire fighting information. See the Hazard Identification Section for Significant Hazards. See Section 4 for First Aid Advice. See Section 8 for advice on the minimum requirements for personal protective equipment. Additional protective measures may be necessary, depending on the specific circumstances and/or the expert judgment of the emergency responders.

#### B. Environmental Precautions and Protective Procedure

In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations.

**Large Spills:** Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

#### C. Methods and Materials for Containment and Cleaning Up

**Land Spill:** Stop leak if you can do it without risk. Recover by pumping or with suitable absorbent.

**Water Spill:** Stop leak if you can do it without risk. Confine the spill immediately with booms. Warn other shipping. Remove from the surface by skimming or with suitable absorbents. Seek the advice of a specialist before using dispersants.

Water spill and land spill recommendations are based on the most likely spill scenario for this material; however, geographic conditions, wind, temperature, (and in the case of a water spill) wave and current direction and speed may greatly influence the appropriate action to be taken. For this reason, local experts should be consulted. Note: Local regulations may prescribe or limit action to be taken.

<b>SECTION 7</b>	<b>HANDLING AND STORAGE</b>
------------------	-----------------------------

#### A. Precautions for Safe Handling

Prevent small spills and leakage to avoid slip hazard. Material can accumulate static charges which may cause an electrical spark (ignition source). When the material is handled in bulk, an

Product Name: MOBILTHERM 603

Revision Date: 06 Jul 2021

Page 5 of 13

electrical spark could ignite any flammable vapors from liquids or residues that may be present (e.g., during switch-loading operations). Use proper bonding and/or ground procedures. However, bonding and grounds may not eliminate the hazard from static accumulation. Consult local applicable standards for guidance. Additional references include American Petroleum Institute 2003 (Protection Against Ignitions Arising out of Static, Lightning and Stray Currents) or National Fire Protection Agency 77 (Recommended Practice on Static Electricity) or CENELEC CLC/TR 50404 (Electrostatics – Code of practice for the avoidance of hazards due to static electricity).

**Static Accumulator:** This material is a static accumulator.

**B. Conditions for Safe Storage**

The type of container used to store the material may affect static accumulation and dissipation. Do not store in open or unlabelled containers.

**SECTION 8****EXPOSURE CONTROLS AND PERSONAL PROTECTION****A. Exposure Limit Values, Biological Limit Values**

Exposure limits/standards (Note: Exposure limits are not additive)

Substance Name	Form	Limit / Standard			Note	Source	Year
SEVERELY HYDROTREATED HEAVY PARAFFINIC DISTILLATE	Inhalable fraction	TWA	5 mg/m <sup>3</sup>			ACGIH	2020
SOLVENT DEWAXED HEAVY PARAFFINIC DISTILLATE	Inhalable fraction	TWA	5 mg/m <sup>3</sup>			ACGIH	2020

Exposure limits/standards for materials that can be formed when handling this product: When mists/aerosols can occur the following is recommended: 5 mg/m<sup>3</sup> – ACGIH TLV (inhalable fraction).

No biological limits allocated.

**B. Appropriate Engineering Controls**

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Control measures to consider:

No special requirements under ordinary conditions of use and with adequate ventilation.

**C. Personal Protective Equipment**

Product Name: MOBILTHERM 603

Revision Date: 06 Jul 2021

Page 6 of 13

Personal protective equipment selections vary based on potential exposure conditions such as applications, handling practices, concentration and ventilation. Information on the selection of protective equipment for use with this material, as provided below, is based upon intended, normal usage.

**Respiratory Protection:** If engineering controls do not maintain airborne contaminant concentrations at a level which is adequate to protect worker health, an approved respirator may be appropriate. Respirator selection, use, and maintenance must be in accordance with regulatory requirements, if applicable. Types of respirators to be considered for this material include: No special requirements under ordinary conditions of use and with adequate ventilation. Particulate

For high airborne concentrations, use an approved supplied-air respirator, operated in positive pressure mode. Supplied air respirators with an escape bottle may be appropriate when oxygen levels are inadequate, gas/vapor warning properties are poor, or if air purifying filter capacity/rating may be exceeded.

**Eye Protection:** If contact is likely, safety glasses with side shields are recommended.

**Hand Protection:** Any specific glove information provided is based on published literature and glove manufacturer data. Glove suitability and breakthrough time will differ depending on the specific use conditions. Contact the glove manufacturer for specific advice on glove selection and breakthrough times for your use conditions. Inspect and replace worn or damaged gloves. The types of gloves to be considered for this material include: No protection is ordinarily required under normal conditions of use. Nitrile, Viton

**Skin and Body Protection:** Any specific clothing information provided is based on published literature or manufacturer data. The types of clothing to be considered for this material include: No skin protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid skin contact.

**Specific Hygiene Measures:** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

## Environmental Controls

Comply with applicable environmental regulations limiting discharge to air, water and soil. Protect the environment by applying appropriate control measures to prevent or limit emissions.

## SECTION 9

## PHYSICAL AND CHEMICAL PROPERTIES

**Note:** Physical and chemical properties are provided for safety, health and environmental considerations

Product Name: MOBILTHERM 603

Revision Date: 06 Jul 2021

Page 7 of 13

only and may not fully represent product specifications. Contact the Supplier for additional information.

**A. Appearance**

Physical State: Liquid

Color: Pale Yellow

**B. Odor:** Characteristic

**C. Odor Threshold:** N/D

**D. pH:** N/A

**E. Melting Point:** N/A

Freezing Point: N/D

**F. Initial Boiling Point / Range:** > 316° C (600° F)

**G. Flash Point [Method]:** >200° C (392° F)

**H. Evaporation Rate (n-butyl acetate = 1):** N/D

**I. Flammability (Solid, Gas):** N/A

**J. Flammable Limits (Approximate volume % in air):** LEL: 0.9 UEL: 7.0

**K. Vapor Pressure:** < 0.013 kPa (0.1 mm Hg) at 20 ° C

**L. Solubility in Water:** Negligible

**M. Vapor Density (Air = 1):** > 2 at 101 kPa

**N. Relative Density (at 15 ° C):** 0.835

**O. Log Pow (n-Octanol/Water Partition Coefficient):** > 3.5

**P. Autoignition Temperature:** N/D

**Q. Decomposition Temperature:** N/D

**R. Viscosity:** 20.2 cSt (20.2 mm<sup>2</sup>/sec) at 40 ° C | 4.1 cSt (4.1 mm<sup>2</sup>/sec) at 100° C

**S. Molecular Weight:** N/D

**Other Information**

Pour Point: -3° C (26° F)

DMSO Extract (mineral oil only), IP-346: < 3 %wt

SECTION 10	STABILITY AND REACTIVITY
------------	--------------------------

**A. Chemical Stability and Possibility of Hazard Reactions**

Chemical Stability: Material is stable under normal conditions.

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

**B. Conditions to Avoid:** Excessive heat. High energy sources of ignition.

**C. Incompatible Materials:** Strong oxidizers

**D. Hazardous Decomposition Products:** Material does not decompose at ambient temperatures.

SECTION 11	TOXICOLOGICAL INFORMATION
------------	---------------------------

**A. Information on Likely Routes of Exposure**

Product Name: MOBILTHERM 603

Revision Date: 06 Jul 2021

Page 8 of 13

---

No data available

## B. Information on Health Hazards

### Acute Toxicity (Inhalation):

Product

(Rat) 4 hour(s) LC50 > 5000 mg/m<sup>3</sup> (Aerosol) Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 403

Inhalation Irritation: No end point data for material. Negligible hazard at ambient/normal handling temperatures.

### Acute Toxicity (Ingestion):

Product

(Rat) LD50 > 5000 mg/kg Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 401

### Acute Toxicity (Dermal)

Product

(Rabbit) LD50 > 5000 mg/kg Minimally Toxic. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 402

### Skin corrosion/irritation

Product

(Rabbit) Data available. Negligible irritation to skin at ambient temperatures. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 404

### Serious eye damage/irritation

Product

(Rabbit) Data available. May cause mild, short-lasting discomfort to eyes. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 405

### Respiratory sensitization

Product

No end point data for material. Not expected to be a respiratory sensitizer.

### Skin sensitization

Product

Data available. Not expected to be a skin sensitizer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 406

### Carcinogenicity

Product

Data available. Not expected to cause cancer. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 451 453

### Germ cell mutagenicity

Product

Data available. Not expected to be a germ cell mutagen. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 471 473 474 476

### Reproductive toxicity

Product



Product Name: MOBILTHERM 603

Revision Date: 06 Jul 2021

Page 9 of 13

---

Data available. Not expected to be a reproductive toxicant. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 414 421

**Specific target organ toxicity – single exposure**

Product

No end point data for material. Not expected to cause organ damage from a single exposure.

**Specific target organ toxicity – repeat exposure**

Product

Data available. Not expected to cause organ damage from prolonged or repeated exposure. Based on test data for structurally similar materials. Test(s) equivalent or similar to OECD Guideline 408 410 411 412 453

**Aspiration hazard**

Product

Data available. May be fatal if swallowed and enters airways. Based on physico-chemical properties of the material.

**Other Information**

**For the product itself:**

Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary edema.

Base oil severely refined: Not carcinogenic in animal studies. Representative material passes IP-346, Modified Ames test, and/or other screening tests. Dermal and inhalation studies showed minimal effects: lung non-specific infiltration of immune cells, oil deposition and minimal granuloma formation. Not sensitizing in test animals.

**IARC Classification:**

The following ingredients are cited on the lists below: None.

--REGULATORY LISTS SEARCHED--

1 = IARC 1

2 = IARC 2A

3 = IARC 2B

<b>SECTION 12</b>
-------------------

<b>ECOLOGICAL INFORMATION</b>
-------------------------------

The information given is based on data for the material, components of the material, or for similar materials, through the application of bridging principals.

**A. Ecotoxicity**

Material -- Not expected to be harmful to aquatic organisms.

Product Name: MOBILTHERM 603  
Revision Date: 06 Jul 2021  
Page 10 of 13

## B. Persistence and Degradability

### Biodegradation:

Material -- Expected to be inherently biodegradable

## C. Bioaccumulation

Material -- Has the potential to bioaccumulate, however metabolism or physical properties may reduce the bioconcentration or limit bioavailability.

## D. Mobility

Material -- Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids.

Material -- Low potential to migrate through soil.

## E. Other adverse effects: Not applicable

## ECOLOGICAL DATA

### Ecotoxicity

Test	Duration	Organism Type	Test Results
Aquatic - Acute Toxicity	48 hour(s)	Daphnia magna	EL0 1000 - 10000 mg/l: data for similar materials
Aquatic - Acute Toxicity	96 hour(s)	Pimephales promelas	LL0 100 mg/l: data for similar materials
Aquatic - Acute Toxicity	72 hour(s)	Pseudokirchneriella subcapitata	EL0 100 mg/l: data for similar materials
Aquatic - Chronic Toxicity	21 day(s)	Daphnia magna	NOELR 10 - 1000 mg/l: data for similar materials
Aquatic - Chronic Toxicity	72 hour(s)	Pseudokirchneriella subcapitata	NOELR 100 mg/l: data for similar materials

### Persistence, Degradability and Bioaccumulation Potential

Media	Test Type	Duration	Test Results
Water	Ready Biodegradability	28 day(s)	Percent Degraded < 60 : similar material

#### A. Disposal methods

Disposal recommendations based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.

#### B. Disposal precautions

Product is suitable for burning in an enclosed controlled burner for fuel value or disposal by supervised incineration at very high temperatures to prevent formation of undesirable combustion products. Protect the environment. Dispose of used oil at designated sites. Minimize skin contact. Do not mix used oils with solvents, brake fluids or coolants.

**Empty Container Warning** Empty Container Warning (where applicable): Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers without proper instructions. Empty drums should be completely drained and safely stored until appropriately reconditioned or disposed. Empty containers should be taken for recycling, recovery, or disposal through suitably qualified or licensed contractor and in accordance with governmental regulations. DO NOT PRESSURISE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION. THEY MAY EXPLODE AND CAUSE INJURY OR DEATH.

<b>SECTION 14</b>
-------------------

<b>TRANSPORT INFORMATION</b>
------------------------------

**REGULATION ON SHIP-TRANSPORTATION AND STORAGE OF DANGEROUS SUBSTANCES (SEA (IMDG))** Not Regulated for Sea Transport according to IMDG-Code

- A. **UN Number:** Not applicable
- B. **Proper Shipping Name:** Not applicable
- C. **Hazard Class & Division:** Not applicable
- D. **Packing Group:** Not applicable
- E. **Marine Pollutant:** Not applicable
- F. **Special Precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance:** Not applicable

**LAND (ADR/RID)** Not Regulated for Land Transport

- A. **UN Number:** Not applicable
- B. **Proper Shipping Name:** Not applicable
- C. **Hazard Class & Division:** Not applicable
- D. **Packing Group:** Not applicable
- E. **Marine pollutants:** Only applicable for sea transport
- F. **Special Precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance:** Not applicable

**AIR (IATA)** Not Regulated for Air Transport

- A. **UN Number:** Not applicable
- B. **Proper Shipping Name:** Not applicable
- C. **Hazard Class & Division:** Not applicable
- D. **Packing Group:** Not applicable
- E. **Marine pollutants:** Only applicable for sea transport

Product Name: MOBILTHERM 603

Revision Date: 06 Jul 2021

Page 12 of 13

F. Special Precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance: Not applicable

SECTION 15	REGULATORY INFORMATION
------------	------------------------

This material is considered hazardous according to Korean GHS classification criteria.

**Regulatory Status and Applicable Laws and Regulations**

A. Industrial Safety & Health Act : Prohibited, Subject to an Approval for Manufacturing and Controlled Hazardous Substances: None.

B. Chemicals Control Act : Toxic, Banned and Restricted Toxic Chemicals, Authorization substances, Accidental Release Prevention Substances and Priority Existing Chemicals to Registration: None.

C. ACT ON THE SAFETY CONTROL OF HAZARDOUS SUBSTANCES: Category 4. Class 4 petroleum chemicals

D. Waste Control Act: Waste Oil is a designated waste.

E. Other requirements in domestic and other countries

Listed or exempt from listing/notification on the following chemical inventories : AIIC, DSL, ENCS, IECSC, ISHL, KECI, PICCS, TCSI, TSCA

SECTION 16	OTHER INFORMATION
------------	-------------------

A. Information sources and references: Sources of information used in preparing this SDS included one or more of the following: results from in house or supplier toxicology studies, CONCAWE Product Dossiers, publications from other trade associations, such as the EU Hydrocarbon Solvents REACH Consortium, U.S. HPV Program Robust Summaries, the EU IUCLID Data Base, U.S. NTP publications, and other sources, as appropriate.

B. The first Issuing date: 7/30/2018

C. Revision number and latest revision date

Revision Number:2

Revision Date: 06 Jul 2021

D. Others

N/D = Not determined, N/A = Not applicable

KEY TO THE H-CODES CONTAINED IN SECTION 3 OF THIS DOCUMENT (for information only):

Product Name: MOBILTHERM 603

Revision Date: 06 Jul 2021

Page 13 of 13

---

H304: May be fatal if swallowed and enters airways; Aspiration, Cat 1

**THIS SAFETY DATA SHEET CONTAINS THE FOLLOWING REVISIONS:**MSDS reformatted and Implementation of new GHS adoption according to regulation requirements.

---

The information and recommendations contained herein are, to the best of ExxonMobil's knowledge and belief, accurate and reliable as of the date issued. You can contact ExxonMobil to insure that this document is the most current available from ExxonMobil. The information and recommendations are offered for the user's consideration and examination. It is the user's responsibility to satisfy itself that the product is suitable for the intended use. If buyer repackages this product, it is the user's responsibility to insure proper health, safety and other necessary information is included with and/or on the container. Appropriate warnings and safe-handling procedures should be provided to handlers and users. Alteration of this document is strictly prohibited. Except to the extent required by law, re-publication or retransmission of this document, in whole or in part, is not permitted. The term, "ExxonMobil" is used for convenience, and may include any one or more of ExxonMobil Chemical Company, Exxon Mobil Corporation, or any affiliates in which they directly or indirectly hold any interest.

---

DGN: 2011272XKR (1013579)

---